



Printing date 27.11.2024 Version number 303 (replaces version 302) Revision: 27.11.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

· Trade name: Screw locking E-COLL

· Article number: 4317784425650

· UFI: VEJJ-29R6-W908-4Y5R

· 1.2 Relevant identified uses of the substance or mixture and uses advised against

· Sector of Use

SU21 Consumer uses: Private households / general public / consumersSU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

· Product category PC8 Biocidal products

- · Application of the substance / the mixture Adhesives
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

E/D/E - Einkaufsbuero Deutscher Eisenhaendler GmbH EDE Platz 1 D-42389 Wuppertal Germany

Tel. +49 202 6096-0 e-mail: sdb@ede.de

- · Further information obtainable from: Product safety department
- · 1.4 Emergency telephone number:

Poison Control Center Mainz - 24 hour emergency service - phone: +49 (0) 6131/19240

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008

Eye Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H335 May cause respiratory irritation.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)





Printing date 27.11.2024 Version number 303 (replaces version 302) Revision: 27.11.2024

Trade name: Screw locking E-COLL

(Contd. of page 1)

· Hazard pictograms



· Signal word Warning

· Hazard-determining components of labelling:

alpha,alpha-dimethylbenzyl hydroperoxide; cumen hydroperoxide; cumene hydroperoxide methacrylic acid, monoester with propane-1,2-diol 2,2'-Ethylenedioxydiethyl dimethacrylate 2'-phenylacetohydrazide

· Hazard statements

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H335 May cause respiratory irritation.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· Additional information:

Use biocidal products with care. Always read the label and product information before use.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

PBT: Not applicable.vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
CAS: 27813-02-1 EINECS: 248-666-3 Index number: 607-125-00-5 Reg.nr.: 01-2119490226-37-xxxx	methacrylic acid, monoester with propane-1,2-diol • Eye Irrit. 2, H319; Skin Sens. 1, H317	25-50%
CAS: 109-16-0 EINECS: 203-652-6 Reg.nr.: 01-2119969287-21-xxxx	2,2'-Ethylenedioxydiethyl dimethacrylate Skin Sens. 1, H317	10-<25%

(Contd. on page 3)





Printing date 27.11.2024 Version number 303 (replaces version 302) Revision: 27.11.2024

Trade name: Screw locking E-COLL

	(Con	ntd. of page 2)
CAS: 80-15-9 EINECS: 201-254-7 Index number: 617-002-00-8 Reg.nr.: 01-2119475796-19-xxxx	α,α -dimethylbenzyl hydroperoxide Org. Perox. E, H242 Acute Tox. 3, H331	<2.5%
CAS: 114-83-0 EINECS: 204-055-3	2'-phenylacetohydrazide Acute Tox. 3, H301 Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335	0.1-<1%
CAS: 123-31-9 EINECS: 204-617-8 Index number: 604-005-00-4	1,4-dihydroxybenzene Muta. 2, H341; Carc. 2, H351 Eye Dam. 1, H318 Aquatic Acute 1, H400 (M=10) Acute Tox. 4, H302; Skin Sens. 1, H317	<0.1%

· Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation: Supply fresh air.
- · After skin contact:

Immediately wash with water and soap and rinse thoroughly. If skin irritation continues, consult a doctor.

- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing: Drink plenty of water and provide fresh air. Call for a doctor immediately.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- \cdot 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.





Printing date 27.11.2024 Version number 303 (replaces version 302) Revision: 27.11.2024

Trade name: Screw locking E-COLL

(Contd. of page 3)

SECTION 5: Firefighting measures

· 5.1 Extinguishing media

· Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters

· Protective equipment:

Do not inhale explosion gases or combustion gases.

Wear self-contained respiratory protective device.

· Additional information

Collect contaminated fire fighting water separately. It must not enter the sewage system.

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation

Wear protective clothing.

· 6.2 Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow product to reach sewage system or any water course.

Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.

(Contd. on page 5)





Printing date 27.11.2024 Version number 303 (replaces version 302) Revision: 27.11.2024

Trade name: Screw locking E-COLL

(Contd. of page 4)

· Information about fire - and explosion protection:



Keep ignition sources away - Do not smoke.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Store only in the original receptacle.
- · Information about storage in one common storage facility: Store away from oxidising agents.
- · Further information about storage conditions:

Keep container tightly sealed. Protect from frost. Store in dry conditions.

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · 8.1 Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

· DNELs

CAS: 27813-02-1 methacrylic acid, monoester with propane-1,2-diol

Dermal Long term value for employees 4.2 mg/kg bw/Tag /AF-72 (industrial use)

CAS: 109-16-0 2,2'-Ethylenedioxydiethyl dimethacrylate

Dermal Long term value for employees | 13.9 mg/kg bw/Tag /AF-72 (industrial use)

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see section 7.
- · Individual protection measures, such as personal protective equipment
- · General protective and hygienic measures:

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the skin.

Avoid contact with the eyes.

(Contd. on page 6)





Version number 303 (replaces version 302) Revision: 27.11.2024 Printing date 27.11.2024

Trade name: Screw locking E-COLL

(Contd. of page 5)

· Respiratory protection:

Not necessary if room is well-ventilated. Use suitable respiratory protective device in case of insufficient ventilation. Short term filter device: Filter A/P2

· Hand protection



· Material of gloves

Nitrile rubber, NBR

Recommended thickness of the material: \geq 0.4 mm

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye/face protection Recommendation: safety glasses with side protection shield

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Colour: Dark blue · Odour: Characteristic · Odour threshold: Not determined. · Melting point/freezing point: Undetermined.

· Boiling point or initial boiling point and boiling

range 240 °C

 Flammability Not applicable.

· Lower and upper explosion limit

Not determined. · Lower: · Upper: Not determined. · Flash point: 96 °C

· Decomposition temperature: Not determined.

· pH at 20 °C 3.5

· Viscosity:

· Kinematic viscosity at 20 °C 1,810-7,143 mm²/s

Kinematic: 23 °C - 4 mm (ISO 2431)

· Dynamic at 20 °C: 1,900-7,500 mPas

· Solubility

· water: Not miscible or difficult to mix.

· Partition coefficient n-octanol/water (log value) Not determined. · Vapour pressure: Not determined.

Density and/or relative density

 Density at 20 °C: 1.05 g/cm³

(Contd. on page 7)





Printing date 27.11.2024 Version number 303 (replaces version 302) Revision: 27.11.2024

Trade name: Screw locking E-COLL

(Contd. of page 6)

Relative densityVapour densityNot determined.Not determined.

· 9.2 Other information

· Appearance:

· Form: Pasty

· Important information on protection of health

and environment, and on safety.

• **Ignition temperature:** Product is not selfigniting.

• Explosive properties: Product does not present an explosion hazard.

Solvent separation test:

· Organic solvents: 0.0 %

· VOC (EC) g/l

· VOCV (CH) 0.0 % 0,00 %

· Solids content: 50.0 %

· Change in condition

· Drip point:

Oxidising propertiesEvaporation rateNot determined.Not determined.

· Information with regard to physical hazard

classes · Explosives Void · Flammable gases Void · Aerosols Void · Oxidising gases Void · Gases under pressure Void · Flammable liquids Void · Flammable solids Void · Self-reactive substances and mixtures Void Pyrophoric liquids Void

Pyrophoric solids
 Self-heating substances and mixtures
 Substances and mixtures, which emit flammable gases in contact with water
 Oxidising liquids
 Void

Oxidising solids
Organic peroxides
Corrosive to metals
Desensitised explosives

Void
Void

SECTION 10: Stability and reactivity

• 10.1 Reactivity No further relevant information available.

(Contd. on page 8)





Printing date 27.11.2024 Version number 303 (replaces version 302) Revision: 27.11.2024

Trade name: Screw locking E-COLL

(Contd. of page 7)

- · 10.2 Chemical stability
- \cdot Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

· 10.3 Possibility of hazardous reactions

Reacts with strong acids and oxidising agents. Danger of polymerisation.

- 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:			
CAS: 278	CAS: 27813-02-1 methacrylic acid, monoester with propane-1,2-diol		
Oral	LD50	>2,000 mg/kg (rat) (OCED 401)	
Dermal	LD50	>5,000 mg/kg (rabbit)	
CAS: 80-1	CAS: 80-15-9 α,α -dimethylbenzyl hydroperoxide		
Oral	LD50	382 mg/kg (rat)	
Dermal	LD50	500 mg/kg (rat)	
Inhalative	LC50/4h	220 ppm (rat)	
CAS: 114-83-0 2'-phenylacetohydrazide			
Oral	LD50	270 mg/kg (mouse)	
CAS: 123-	CAS: 123-31-9 1,4-dihydroxybenzene		
Oral	LD50	320 mg/kg (rat)	
Dermal	LD50	>2,000 mg/kg (rabbit)	

- · Primary irritant effect:
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- Serious eye damage/irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

May cause an allergic skin reaction.

· Germ cell mutagenicity Based on available data, the classification criteria are not met.

(Contd. on page 9)





Printing date 27.11.2024 Version number 303 (replaces version 302) Revision: 27.11.2024

Trade name: Screw locking E-COLL

(Contd. of page 8)

- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure

May cause respiratory irritation.

- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.
- · 11.2 Information on other hazards
- · Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity:		
CAS: 80-15-9 α,α -dimethylbenzyl hydroperoxide		
LC50 (96h)	3.9 mg/L (Oncorhynchus mykiss)	
EC50/24h	7 mg/l (daphnia)	
CAS: 123-31-9 1,4-dihydroxybenzene		
EC50/24h	0.12 mg/l (daphnia)	
96h LC50	0.044 mg/l (Pimephales promelas)	

- · 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

- · 12.7 Other adverse effects
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:

Harmful to aquatic organisms

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water





Printing date 27.11.2024 Version number 303 (replaces version 302) Revision: 27.11.2024

Trade name: Screw locking E-COLL

(Contd. of page 9)

Do not allow product to reach ground water, water course or sewage system.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods:

Containers can be recycled if completely empty; if not, dispose product/containers as dangerous waste. Observe local regulations.

Recommendation

Completely emptied packagings can be given for recycling. (In accordance with local authority regulations, take to chemical/physical treatment plant.)

· European waste catalogue

08 04 09* waste adhesives and sealants containing organic solvents or other hazardous substances

SECTION 14: Transport information

· 14.1 UN number or ID number

· ADR, ADN, IMDG, IATA Void

14.2 UN proper shipping name

· ADR, ADN, IMDG, IATA Void

· 14.3 Transport hazard class(es)

· ADR, ADN, IMDG, IATA

· Class Void

· 14.4 Packing group

· ADR, IMDG, IATA Void

· 14.5 Environmental hazards:

· Marine pollutant: No

• 14.6 Special precautions for user Not applicable.

· 14.7 Maritime transport in bulk according to IMO

instruments Not applicable.

· Transport/Additional information:

· IMDG

• Remarks: No dangerous goods in receptacles with a capacity not

exceeding 450 litres according to IMDG 2.3.2.5

UN "Model Regulation": Void

SECTION 15: Regulatory information

• 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

(Contd. on page 11)





Printing date 27.11.2024 Version number 303 (replaces version 302) Revision: 27.11.2024

Trade name: Screw locking E-COLL

(Contd. of page 10)

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms



Signal word Warning

· Hazard-determining components of labelling:

methacrylic acid, monoester with propane-1,2-diol 2,2'-Ethylenedioxydiethyl dimethacrylate

2'-phenylacetohydrazide

· Hazard statements

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H335 May cause respiratory irritation.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Chemical safety assessment
- Named dangerous substances ANNEX I Methanol

· REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

· DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

· REGULATION (EU) 2019/1148

· Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

· Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

· Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

 Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

- · National regulations:
- · Verordnung (EU) Nr. 528/2012 Verwendung von Biozidprodukten applicable

(Contd. on page 12)





Printing date 27.11.2024 Version number 303 (replaces version 302) Revision: 27.11.2024

Trade name: Screw locking E-COLL

(Contd. of page 11)

· Information about limitation of use:

Employment restrictions concerning pregnant and lactating women must be observed.

· Exposure scenario(s)

Exposure scenario(s) of ingredients (if present) are available on request at: sdb@ede.de

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H242 Heating may cause a fire.

H301 Toxic if swallowed.

H302 Harmful if swallowed.

H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H331 Toxic if inhaled.

H335 May cause respiratory irritation.

H341 Suspected of causing genetic defects.

H351 Suspected of causing cancer.

H373 May cause damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H411 Toxic to aquatic life with long lasting effects.

· Department issuing SDS: Product safety department

· Contact: sdb@ede.de

Date of previous version: 27.11.2024
Version number of previous version: 302

· Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the

International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOCV: Lenkungsabgabe auf flüchtigen organischen Verbindungen, Schweiz (Swiss Ordinance on volatile organic compounds)

DNEL: Derived No-Effect Level (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Org. Perox. E: Organic peroxides - Type E/F

Acute Tox. 4: Acute toxicity – Category 4 Acute Tox. 3: Acute toxicity – Category 3

Skin Corr. 1B: Skin corrosion/irritation - Category 1B

Skin Irrit. 2: Skin corrosion/irritation – Category 2





Printing date 27.11.2024 Version number 303 (replaces version 302) Revision: 27.11.2024

Trade name: Screw locking E-COLL

(Contd. of page 12)

Eye Dam. 1: Serious eye damage/eye irritation - Category 1 Eye Irrit. 2: Serious eye damage/eye irritation - Category 2

Skin Sens. 1: Skin sensitisation – Category 1

Muta. 2: Germ cell mutagenicity – Category 2

Carc. 2: Carcinogenicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 STOT RE 2: Specific target organ toxicity (repeated exposure) - Category 2

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2

· * Data compared to the previous version altered.

EU —