

Printing date 18.03.2024 Version number 304 (replaces version 303) Revision: 18.03.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

100.00 %

· 1.1 Product identifier

· Trade name: Special superglue remover E-COLL

· Article number: 4317784465076

· UFI: JYHJ-J997-C90T-T88E

1.2 Relevant identified uses of the substance or mixture and uses advised against

· Sector of Use

SU21 Consumer uses: Private households / general public / consumers

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

- · Application of the substance / the mixture Solvents
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

E/D/E - Einkaufsbuero Deutscher Eisenhaendler GmbH EDE Platz 1 D-42389 Wuppertal Germany

Tel. +49 202 6096-0 e-mail: sdb@ede.de

- · Further information obtainable from: Product safety department
- 1.4 Emergency telephone number: Giftinformationszentrum Mainz Tel.: +49 (6131) 19240

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008

Flam. Liq. 2 H225 Highly flammable liquid and vapour.

Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

- · 2.2 Label elements
- Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms





GHS02 GHS07

· Signal word Danger



Printing date 18.03.2024 Version number 304 (replaces version 303) Revision: 18.03.2024

Trade name: Special superglue remover E-COLL

(Contd. of page 1)

· Hazard-determining components of labelling:

acetone ethyl acetate

· Hazard statements

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

· Precautionary statements

i redutionally statements		
P101	If medical advice is needed, have product container or label at hand.	
P102	Keep out of reach of children.	
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.	
P243	Take action to prevent static discharges.	
P271	Use only outdoors or in a well-ventilated area.	
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.	

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P337+P313 If eye irritation persists: Get medical advice/attention.
P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking.

Product contains: Reportable explosives precursors. Making available, introduction, possession and use according to Regulation (EU) 2019/1148, Article 9.

· 2.3 Other hazards

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

	· Dangerous components:					
Ī	CAS: 67-64-1	acetone	50-100%			
	EINECS: 200-662-2	♦ Flam. Liq. 2, H225				
	Index number: 606-001-00-8	♦ Eye Irrit. 2, H319; STOT SE 3, H336				
	Reg.nr.: 01-2119471330-49-xxxx	EUH066				
	01-2119498062-37-xxxx					
Ī	CAS: 141-78-6	ethyl acetate	25-50%			
	EINECS: 205-500-4	♦ Flam. Liq. 2, H225				
	Index number: 607-022-00-5	(t) Eye Irrit. 2, H319; STOT SE 3, H336				
	Reg.nr.: 01-2119475103-46-xxxx	EUH066				
	(Contd. on page 3)					

(Contd. on page 3)



Printing date 18.03.2024 Version number 304 (replaces version 303) Revision: 18.03.2024

Trade name: Special superglue remover E-COLL

(Contd. of page 2)

· Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information: Personal protection for the First Aider.
- After inhalation:

Supply fresh air.

Seek medical treatment in case of complaints.

- · After skin contact: If skin irritation continues, consult a doctor.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· After swallowing:

Rinse out mouth and then drink plenty of water.

Do not induce vomiting; call for medical help immediately.

· 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

· 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters
- · Protective equipment:

Do not inhale explosion gases or combustion gases.

Wear self-contained respiratory protective device.

· Additional information Cool endangered receptacles with water spray.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Keep away from ignition sources.

(Contd. on page 4)



Printing date 18.03.2024 Version number 304 (replaces version 303) Revision: 18.03.2024

Trade name: Special superglue remover E-COLL

(Contd. of page 3)

- 6.2 Environmental precautions: Prevent seepage into sewage system, workpits and cellars.
- · 6.3 Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

- 7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.
- · Information about fire and explosion protection:



Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Fumes can combine with air to form an explosive mixture.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Provide floor trough without outlet.
- · Information about storage in one common storage facility: Store away from oxidising agents.
- · Further information about storage conditions:

Keep container tightly sealed.

Protect from heat and direct sunlight.

Store in a cool place.

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

CAS: 67-64-1 acetone

IOELV Long-term value: 1210 mg/m³, 500 ppm

CAS: 141-78-6 ethyl acetate

IOELV Short-term value: 1468 mg/m³, 400 ppm Long-term value: 734 mg/m³, 200 ppm

· Additional information: The lists valid during the making were used as basis.

(Contd. on page 5)



Printing date 18.03.2024 Version number 304 (replaces version 303) Revision: 18.03.2024

Trade name: Special superglue remover E-COLL

(Contd. of page 4)

- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see section 7.
- · Individual protection measures, such as personal protective equipment

· General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed. Wash hands before breaks and at the end of work. Do not inhale gases / fumes / aerosols. Avoid contact with the eyes and skin.

· Respiratory protection:

Not necessary if room is well-ventilated. Use suitable respiratory protective device in case of insufficient ventilation. Self-contained respiratory protective device.

Hand protection



Protective gloves

Material of gloves

Butyl rubber, BR

Recommended thickness of the material: ≥ 0.4 mm

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

56 °C

· Eye/face protection



Tightly sealed goggles

· Body protection: Protective work clothing

SECTION 9: Physical and chemical properties

- · 9.1 Information on basic physical and chemical properties
- · General Information

Colour:
 Odour:
 Odour threshold:
 Melting point/freezing point:
 Colourless

 Characteristic
 Not determined.

 Undetermined.

· Boiling point or initial boiling point and boiling

range

Flammability
 Not applicable.

· Lower and upper explosion limit

• **Lower:** 2.1 Vol %

(Contd. on page 6)



Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 18.03.2024 Version number 304 (replaces version 303) Revision: 18.03.2024

Trade name: Special superglue remover E-COLL

(Contd. of page 5)

· Upper: 13.0 Vol %
· Flash point: -19 °C
· Auto-ignition temperature: 460 °C

Decomposition temperature: Not determined.pH Not determined.

· Viscosity:

· Kinematic viscosity Not determined.

· Kinematic: 23 °C - 4 mm (ISO 2431)

· **Dynamic:** Not determined.

Solubility

water: Fully miscible.
 Partition coefficient n-octanol/water (log value)
 Not determined.

· Vapour pressure at 20 °C: 233 hPa

· Density and/or relative density

Density at 20 °C: 0.82 g/cm³
 Relative density Not determined.
 Vapour density Not determined.

· 9.2 Other information

· Appearance:

· Form: Fluid

· Important information on protection of health and environment, and on safety.

· **Ignition temperature:** Product is not selfigniting.

• Explosive properties: Product is not explosive. However, formation of

explosive air/vapour mixtures are possible.

· Solvent separation test:

Organic solvents: 100.0 %
 VOC (EC) % 100.00 %
 VOC (EC) g/I 820.0 g/I

Change in condition

· Corrosive to metals

· Drip point:

Oxidising propertiesEvaporation rateNot determined.Not determined.

Information with regard to physical hazard classes

Explosives Void
Flammable gases Void
Aerosols Void
Oxidising gases Void
Gases under pressure Void

· Flammable liquids Highly flammable liquid and vapour.

Void

· Flammable solids Void · Self-reactive substances and mixtures Void · Pyrophoric liquids Void · Pyrophoric solids Void · Self-heating substances and mixtures Void · Substances and mixtures, which emit flammable gases in contact with water Void Oxidising liquids Void · Oxidising solids Void · Organic peroxides Void

(Contd. on page 7)



Printing date 18.03.2024 Version number 304 (replaces version 303) Revision: 18.03.2024

Trade name: Special superglue remover E-COLL

(Contd. of page 6)

· Desensitised explosives

Void

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:						
CAS: 67-64-1 acetone						
Oral	LD50	5,800 mg/kg (rat)				
Dermal	LD50	20,000 mg/kg (rabbit)				
Inhalative	LC50/4h	76 mg/m³ (rat)				
CAS: 141-78-6 ethyl acetate						
Oral	LD50	5,620 mg/kg (rabbit)				
Inhalative	LC50/4h	1,600 ppm (rat)				

- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation

Causes serious eye irritation.

- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure

May cause drowsiness or dizziness.

· STOT-repeated exposure Based on available data, the classification criteria are not met.

(Contd. on page 8)



Printing date 18.03.2024 Version number 304 (replaces version 303) Revision: 18.03.2024

Trade name: Special superglue remover E-COLL

(Contd. of page 7)

- · Aspiration hazard Based on available data, the classification criteria are not met.
- · 11.2 Information on other hazards
- · Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity:					
CAS: 67-64	CAS: 67-64-1 acetone				
LC50 (96h)	5,000 mg/L (Lepomis macrochirus)				
LC50/48h	8,800 mg/l (Daphnia magna)				
NOEC	430 mg/l (algae)				
NOEC/16h	1,700 mg/l (Pseudomonas putida)				
NOEC/48h	4,740 mg/l (Pseudokirchneriella subcapitata)				
96h LC50	5,540 mg/l (Oncorhynchus mykiss)				

- · 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

- · 12.7 Other adverse effects
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods:

Containers can be recycled if completely empty; if not, dispose product/containers as dangerous waste. Observe local regulations.

· European waste catalogue		
16 00 00	WASTES NOT OTHERWISE SPECIFIED IN THE LIST	
16 05 00	gases in pressure containers and discarded chemicals	

(Contd. on page 9)



Printing date 18.03.2024 Version number 304 (replaces version 303) Revision: 18.03.2024

Trade name: Special superglue remover E-COLL

	[1]	Contd. of page 8)
16 05 04*	gases in pressure containers (including halons) containing hazardous substances	
HP3	Flammable	
HP4	Irritant - skin irritation and eye damage	
HP5	Specific Target Organ Toxicity (STOT)/Aspiration Toxicity	

· Recommended cleansing agents: Water, if necessary together with cleansing agents.

SECTION 14: Transport information

· 14.1 UN number or ID number

· ADR, IMDG, IATA UN1993

· 14.2 UN proper shipping name

UN1993 FLAMMABLE LIQUID, N.O.S. (ACETONE, · ADR

ETHYL ACETATE)

· IMDG, IATA FLAMMABLE LIQUID, N.O.S. (ACETONE, ETHYL

ACETATE)

· 14.3 Transport hazard class(es)

· ADR



3 (F1) Flammable liquids. · Class

· Label

· IMDG, IATA



· Class 3 Flammable liquids.

· Label 3

· 14.4 Packing group

· ADR, IMDG, IATA Ш

· 14.5 Environmental hazards: Not applicable.

· 14.6 Special precautions for user Warning: Flammable liquids.

· Hazard identification number (Kemler code):

F-E,<u>S-E</u>

33

· EMS Number:

 Stowage Category В

14.7 Maritime transport in bulk according to IMO

instruments Not applicable.

(Contd. on page 10)



Printing date 18.03.2024 Version number 304 (replaces version 303) Revision: 18.03.2024

Trade name: Special superglue remover E-COLL

(Contd. of page 9)

· Transport/Additional information:

· ADR

· Limited quantities (LQ) 1L

· Excepted quantities (EQ) Code: E2

Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml

Transport categoryTunnel restriction codeD/E

· IMDG

Limited quantities (LQ)Excepted quantities (EQ)Code: E2

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per niner packaging: 500 ml

• UN 1993 FLAMMABLE LIQUID, N.O.S. (ACETONE,

ETHYL ACETATE), 3, II

SECTION 15: Regulatory information

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

· Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms





GHS02 GHS07

· Signal word Danger

· Hazard-determining components of labelling:

acetone ethyl acetate

· Hazard statements

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P243 Take action to prevent static discharges.
P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing

protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P337+P313 If eye irritation persists: Get medical advice/attention.

(Contd. on page 11)



Printing date 18.03.2024 Version number 304 (replaces version 303) Revision: 18.03.2024

Trade name: Special superglue remover E-COLL

(Contd. of page 10)

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

- Directive 2012/18/EU
- Seveso category P5c FLAMMABLE LIQUIDS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 5.000 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 50.000 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- · DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment Annex II

None of the ingredients is listed.

- · REGULATION (EU) 2019/1148
- · Annex I RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

· Annex II - REPORTABLE EXPLOSIVES PRECURSORS

CAS: 67-64-1 acetone

· Regulation (EC) No 273/2004 on drug precursors

CAS: 67-64-1 acetone

3

· Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

CAS: 67-64-1 acetone

3

Exposure scenario(s)

Exposure scenario(s) of ingredients (if present) are available on request at: sdb@ede.de

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

EUH066 Repeated exposure may cause skin dryness or cracking.

· Contact: sdb@ede.de

Date of previous version: 11.01.2024
 Version number of previous version: 303

Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

Page 12/12



Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 18.03.2024 Version number 304 (replaces version 303) Revision: 18.03.2024

Trade name: Special superglue remover E-COLL

(Contd. of page 11)

CAS: Chemical Abstracts Service (division of the American Chemical Society) VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 2: Flammable liquids – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

· * Data compared to the previous version altered.

EU -