



Printing date 22.01.2025 Version number 304 (replaces version 303) Revision: 22.01.2025

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier 600094

· Trade name: Paint Removal Fluid E-COLL

· Article number: 4317784496773

· UFI: 7YGQ-0A6D-QA0A-1XP0

1.2 Relevant identified uses of the substance or mixture and uses advised against

· Sector of Use

SU21 Consumer uses: Private households / general public / consumers

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

- · Application of the substance / the mixture Paint remover
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

E/D/E - Einkaufsbuero Deutscher Eisenhaendler GmbH EDE Platz 1 D-42389 Wuppertal Germany

Tel. +49 202 6096-0 e-mail: sdb@ede.de

- · Further information obtainable from: Product safety department
- · 1.4 Emergency telephone number:

Poison Control Center Mainz - 24 hour emergency service - phone: +49 (0) 6131/19240

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008

Met. Corr.1 H290 May be corrosive to metals.

Acute Tox. 4 H302 Harmful if swallowed.

Acute Tox. 4 H332 Harmful if inhaled.

Skin Irrit. 2 H315 Causes skin irritation.

Eye Dam. 1 H318 Causes serious eye damage.

· 2.2 Label elements

· Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)





Printing date 22.01.2025 Version number 304 (replaces version 303) Revision: 22.01.2025

Trade name: Paint Removal Fluid E-COLL

(Contd. of page 1)

· Hazard pictograms





GHS05 GHS07

· Signal word Danger

· Hazard-determining components of labelling:

benzyl alcohol formic acid

POLYOXYETHYLENE PHENYL ETHER PHOSPHAT

· Hazard statements

H290 May be corrosive to metals. H302+H332 Harmful if swallowed or if inhaled.

H315 Causes skin irritation.

H318 Causes serious eye damage.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P264 Wash thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.
P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing

protection.

P301+P312 IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell.

P302+P352 IF ON SKIN: Wash with plenty of water.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P406 Store in a corrosion resistant container / container with a resistant inner liner.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

The product does not meet the PBT and vPvB classification criteria Contains no PBT and/or vPvB substances ≥ 0.1%, assessed according to REACH Annex XIII

- · PBT: Not applicable.
- · vPvB: Not applicable.





Printing date 22.01.2025 Version number 304 (replaces version 303) Revision: 22.01.2025

Trade name: Paint Removal Fluid E-COLL

(Contd. of page 2)

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:			
CAS: 100-51-6 EINECS: 202-859-9 Index number: 603-057-00-5 Reg.nr.: 01-2119492630-38	benzyl alcohol Acute Tox. 4, H302; Acute Tox. 4, H332; Eye Irrit. 2, H319 ATE: LD50 oral: 1,200 mg/kg	>50-<100%	
CAS: 64-18-6 EINECS: 200-579-1 Index number: 607-001-00-0 Reg.nr.: 01-2119491174-37	formic acid	>2.5-<10%	
CAS: 39464-70-5 EC number: 609-691-9 Reg.nr.: 01-2120771013-65	POLYOXYETHYLENE PHENYL ETHER PHOSPHAT Eye Dam. 1, H318	>1-<2.5%	
· Non-hazardous components			
CAS: 7631-86-9 silicon dioxide, chemically prepared EINECS: 231-545-4		2.5-10%	

· Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

· General information: Immediately remove any clothing soiled by the product.

· After inhalation:

Supply fresh air.

Seek medical treatment in case of complaints.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly. If skin irritation continues, consult a doctor.

· After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.

· After swallowing:

Do not induce vomiting; call for medical help immediately.

(Contd. on page 4)





Version number 304 (replaces version 303) Revision: 22.01.2025 Printing date 22.01.2025

Trade name: Paint Removal Fluid E-COLL

(Contd. of page 3)

Drink plenty of water and provide fresh air. Call for a doctor immediately.

· 4.2 Most important symptoms and effects, both acute and delayed

Dizziness Headache Nausea

· 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- 5.1 Extinguishing media
- · Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.
- 5.2 Special hazards arising from the substance or mixture

In case of fire, the following can be released:

Carbon monoxide (CO)

- · 5.3 Advice for firefighters
- · Protective equipment:

Do not inhale explosion gases or combustion gases.

Mouth respiratory protective device.

· Additional information

Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Wear protective clothing.
- 6.2 Environmental precautions: No special measures required.
- · 6.3 Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

• 7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.

(Contd. on page 5)





Printing date 22.01.2025 Version number 304 (replaces version 303) Revision: 22.01.2025

Trade name: Paint Removal Fluid E-COLL

(Contd. of page 4)

· Information about fire - and explosion protection:

Fumes can combine with air to form an explosive mixture.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Provide floor trough without outlet. Store only in the original receptacle.

- · Information about storage in one common storage facility: Store away from oxidising agents.
- · Further information about storage conditions: Keep container tightly sealed.
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · 8.1 Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see section 7.
- · Individual protection measures, such as personal protective equipment
- · General protective and hygienic measures:

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the skin.

Avoid contact with the eyes.

· Respiratory protection:

Use suitable respiratory protective device only when aerosol or mist is formed.

Filter: ABEK

· Hand protection







Printing date 22.01.2025 Version number 304 (replaces version 303) Revision: 22.01.2025

Trade name: Paint Removal Fluid E-COLL

(Contd. of page 5)

· Material of gloves

Butyl rubber, BR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

Recommended thickness of the material: ≥ 0.4 mm

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye/face protection



Tightly sealed goggles / face protection.

· Body protection:

Acid resistant protective clothing Protective work clothing

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

Physical state pastyColour: Yellow

Odour: Characteristic
 Odour threshold: Not determined.
 Melting point/freezing point: Undetermined.

 \cdot Boiling point or initial boiling point and boiling

range 100-210 °C • Flammability Not applicable.

 \cdot Lower and upper explosion limit

Lower: Not determined.
Upper: Not determined.
Flash point: 85 °C

• Auto-ignition temperature: 85 °C 200 °C

• **Decomposition temperature:** Not determined.

• pH at 20 °C 2.9-3.9

· Viscosity:

· Kinematic viscosity Not determined.

· Kinematic: 23 °C - 4 mm (ISO 2431)

· **Dynamic:** Not determined.

· Solubility

• water: Not miscible or difficult to mix.

· Partition coefficient n-octanol/water (log value) Not determined.

• Vapour pressure at 20 °C: Not determined 0.9 hPa

· Density and/or relative density

• Density at 20 °C: 1.01-1.07 g/cm³

(Contd. on page 7)





Printing date 22.01.2025 Version number 304 (replaces version 303) Revision: 22.01.2025

Trade name: Paint Removal Fluid E-COLL

(Contd. of page 6)

Relative densityVapour densityNot determined.Not determined.

· 9.2 Other information

· Appearance:

· Form: Pasty

Important information on protection of health

and environment, and on safety.

• Ignition temperature: Product is not selfigniting.

• Explosive properties: Product does not present an explosion hazard.

⋅ VOC (EC) g/l
⋅ VOCV (CH)
<132.0 g/l</p>
0,00 %

· Change in condition

· Drip point:

Oxidising propertiesEvaporation rateNot determined.Not determined.

 \cdot Information with regard to physical hazard

classes

· Explosives Void · Flammable gases Void · Aerosols Void · Oxidising gases Void · Gases under pressure Void · Flammable liquids Void · Flammable solids Void · Self-reactive substances and mixtures Void · Pyrophoric liquids Void · Pyrophoric solids Void Void Self-heating substances and mixtures · Substances and mixtures, which emit flammable gases in contact with water Void Oxidising liquids Void · Oxidising solids Void · Organic peroxides Void

• Corrosive to metals May be corrosive to metals.

Desensitised explosives

Void

SECTION 10: Stability and reactivity

- 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

· 10.3 Possibility of hazardous reactions No dangerous reactions known.

(Contd. on page 8)





Printing date 22.01.2025 Version number 304 (replaces version 303) Revision: 22.01.2025

Trade name: Paint Removal Fluid E-COLL

(Contd. of page 7)

- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: Carbon monoxide and carbon dioxide

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity

Harmful if swallowed or if inhaled.

· LD/LC50 values relevant for classification:		
CAS: 100-51-6 benzyl alcohol		
Oral	LD50	1,200 mg/kg (ATE)
		1,230 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (rabbit)
Inhalative	LC50/4h	>4,178 mg/m³ (rat)
CAS: 64-18-6 formic acid		
Oral	LD50	1,100 mg/kg (rat)
Inhalative	LC50/4h	7.4 mg/m³ (rat)

- · Primary irritant effect:
- · Skin corrosion/irritation

Causes skin irritation.

· Serious eye damage/irritation

Causes serious eye damage.

- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

(Contd. on page 9)





Printing date 22.01.2025 Version number 304 (replaces version 303) Revision: 22.01.2025

Trade name: Paint Removal Fluid E-COLL

(Contd. of page 8)

- · 11.2 Information on other hazards
- · Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- 12.6 Endocrine disrupting properties For information on endocrine disrupting properties see section 11.
- · 12.7 Other adverse effects
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods:

Containers can be recycled if completely empty; if not, dispose product/containers as dangerous waste. Observe local regulations.

· European waste catalogue

08 01 17* wastes from paint or varnish removal containing organic solvents or other hazardous substances

SECTION 14: Transport information

- · 14.1 UN number or ID number
- · ADR, IMDG, IATA

UN3265

(Contd. on page 10)





Printing date 22.01.2025 Version number 304 (replaces version 303) Revision: 22.01.2025

Trade name: Paint Removal Fluid E-COLL

(Contd. of page 9)

· 14.2 UN proper shipping name

· ADR UN3265 CORROSIVE LIQUID, ACIDIC, ORGANIC,

N.O.S. (FORMIC ACID)

· IMDG, IATA CORROSIVE LIQUID, ACIDIC, ORGANIC, N.O.S.

(FORMIC ACID)

· 14.3 Transport hazard class(es)

· ADR



· Class 8 (C3) Corrosive substances.

· Label 8

· IMDG, IATA



· Class 8 Corrosive substances.

· Label 8

· 14.4 Packing group

· ADR, IMDG, IATA

· 14.5 Environmental hazards:

· Marine pollutant: No

• 14.6 Special precautions for user Warning: Corrosive substances.

Hazard identification number (Kemler code):
 EMS Number:
 Segregation groups
 Stowage Category

80
F-A,S-B
Acids
A

• Stowage Code SW2 Clear of living quarters.

• **Segregation Code**SG36 Stow "separated from" SGG18-alkalis.
SG49 Stow "separated from" SGG6-cyanides

· 14.7 Maritime transport in bulk according to IMO

instruments Not applicable.

· Transport/Additional information:

· ADR

Limited quantities (LQ)Excepted quantities (EQ)5LCode: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

· Transport category

(Contd. on page 11)





Printing date 22.01.2025 Version number 304 (replaces version 303) Revision: 22.01.2025

E

Trade name: Paint Removal Fluid E-COLL

(Contd. of page 10)

· Tunnel restriction code

· IMDG

Limited quantities (LQ)
 Excepted quantities (EQ)
 5L
 Code: E1

Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml UN 3265 CORROSIVE LIQUID, ACIDIC, ORGANIC,

N.O.S. (FORMIC ACID), 8, III

SECTION 15: Regulatory information

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

· Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms

· UN "Model Regulation":





GHS05 GHS07

Signal word Danger

· Hazard-determining components of labelling:

benzyl alcohol formic acid

POLYOXYETHYLENE PHENYL ETHER PHOSPHAT

· Hazard statements

H290 May be corrosive to metals. H302+H332 Harmful if swallowed or if inhaled.

H315 Causes skin irritation.

H318 Causes serious eye damage.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P264 Wash thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.
P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing

protection.

P301+P312 IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell.

P302+P352 IF ON SKIN: Wash with plenty of water.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P406 Store in a corrosion resistant container / container with a resistant inner liner.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

(Contd. on page 12)





Printing date 22.01.2025 Version number 304 (replaces version 303) Revision: 22.01.2025

Trade name: Paint Removal Fluid E-COLL

(Contd. of page 11)

- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- · National regulations:
- · Information about limitation of use:

Employment restrictions concerning pregnant and lactating women must be observed.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H226 Flammable liquid and vapour.

H302 Harmful if swallowed.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H331 Toxic if inhaled.

H332 Harmful if inhaled.

· Department issuing SDS: Product safety department

Contact: Head of Product Safety Department

· Date of previous version: 25.11.2021

· Version number of previous version: 303

· Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOCV: Lenkungsabgabe auf flüchtigen organischen Verbindungen, Schweiz (Swiss Ordinance on volatile organic compounds)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

ATE: Acute toxicity estimate values

Flam. Liq. 3: Flammable liquids – Category 3

Met. Corr.1: Corrosive to metals – Category 1

Acute Tox. 4: Acute toxicity – Category 4 Acute Tox. 3: Acute toxicity – Category 3

Skin Corr. 1A: Skin corrosion/irritation - Category 1A

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

· * Data compared to the previous version altered.