



Printing date 25.02.2025 Version number 306 (replaces version 305) Revision: 25.02.2025

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier 600142

· Trade name: One-Component Multi-Primer E-COLL

· Article number: 4317784305471

· UFI: J12R-V402-1C0Y-J48N

· 1.2 Relevant identified uses of the substance or mixture and uses advised against

· Sector of Use

SU21 Consumer uses: Private households / general public / consumers

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

- · Application of the substance / the mixture Anticorrosion additive
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

E/D/E - Einkaufsbuero Deutscher Eisenhaendler GmbH EDE Platz 1 D-42389 Wuppertal Germany

Tel. +49 202 6096-0 e-mail: sdb@ede.de

- · Further information obtainable from: Product safety department
- · 1.4 Emergency telephone number:

Poison Control Center Mainz - 24 hour emergency service - phone: +49 (0) 6131/19240

SECTION 2: Hazards identification

· 2.1 Classification of the substance or mixture

· Classification according to Regulation (EC) No 1272/2008

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

Eye Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H336 May cause drowsiness or dizziness.

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

· 2.2 Label elements

· Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)





Printing date 25.02.2025 Version number 306 (replaces version 305) Revision: 25.02.2025

Trade name: One-Component Multi-Primer E-COLL

(Contd. of page 1)

· Hazard pictograms







GHS02 GHS07 GHS09

· Signal word Danger

· Hazard-determining components of labelling:

n-butyl acetate

 $reaction\ product:\ bisphenol-A-(epichlorhydrin)\ epoxy\ resin\ (number\ average\ molecular\ weight \le 700)$

acetone butan-1-ol

· Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H319 Causes serious eye irritation.
H317 May cause an allergic skin reaction.
H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P261 Avoid breathing spray.

P271 Use only outdoors or in a well-ventilated area.

P273 Avoid release to the environment.

P280 Wear protective gloves / eye protection / face protection.

P302+P352 IF ON SKIN: Wash with plenty of water.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P405 Store locked up.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking. Buildup of explosive mixtures possible without sufficient ventilation.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

PBT: Not applicable.vPvB: Not applicable.





Printing date 25.02.2025 Version number 306 (replaces version 305) Revision: 25.02.2025

Trade name: One-Component Multi-Primer E-COLL

(Contd. of page 2)

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

• **Description:** Mixture of substances listed below with nonhazardous additions.

Description: wixture of description into a select with normalization administration.				
· Dangerous components:				
CAS: 115-10-6 EINECS: 204-065-8 Index number: 603-019-00-8 Reg.nr.: 01-2119472128-37-xxxx	dimethyl ether Flam. Gas 1A, H220	25-50%		
CAS: 123-86-4 EINECS: 204-658-1 Index number: 607-025-00-1 Reg.nr.: 01-2119485493-29-0059		10-<25%		
CAS: 67-64-1 EINECS: 200-662-2 Index number: 606-001-00-8 Reg.nr.: 01-2119471330-49-xxxx 01-2119498062-37-xxxx	acetone Flam. Liq. 2, H225 Eye Irrit. 2, H319; STOT SE 3, H336	10-<25%		
CAS: 1330-20-7 EINECS: 215-535-7 Index number: 601-022-00-9 Reg.nr.: 01-2119488216-32	Xylene ♠ Flam. Liq. 3, H226 ♠ STOT RE 2, H373; Asp. Tox. 1, H304 ♠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335 Aquatic Chronic 3, H412	2.5-10%		
CAS: 1314-13-2 EINECS: 215-222-5 Index number: 030-013-00-7 Reg.nr.: 01-2119463881-32	zinc oxide � Āquatic Acute 1, H400; Aquatic Chronic 1, H410	<2.5%		
CAS: 7779-90-0 EINECS: 231-944-3 Index number: 030-011-00-6 Reg.nr.: 01-2119485044-40	trizinc bis(orthophosphate) Aquatic Acute 1, H400; Aquatic Chronic 1, H410	<2.5%		
CAS: 25068-38-6 NLP: 500-033-5 Index number: 603-074-00-8	reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700) Aquatic Chronic 2, H411 Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317 EUH205 Specific concentration limits: Eye Irrit. 2; H319: C ≥ 5 % Skin Irrit. 2; H315: C ≥ 5 %	<2.5%		
CAS: 71-36-3 EINECS: 200-751-6 Index number: 603-004-00-6 Reg.nr.: 01-2119484630-38-xxxx	butan-1-ol ♠ Flam. Liq. 3, H226 ♠ Eye Dam. 1, H318 ♠ Acute Tox. 4, H302; Skin Irrit. 2, H315; STOT SE 3, H335-H336	<1.25%		

\cdot Regulation (EC) No 648/2004 on detergents / Labelling for contents less than 5 %





Printing date 25.02.2025 Version number 306 (replaces version 305) Revision: 25.02.2025

Trade name: One-Component Multi-Primer E-COLL

(Contd. of page 3)

aromatic hydrocarbons

· Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- General information: Personal protection for the First Aider.
- · After inhalation:

Supply fresh air.

Seek medical treatment in case of complaints.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing:

Rinse out mouth and then drink plenty of water.

If symptoms persist consult doctor.

· 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

· 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · 5.2 Special hazards arising from the substance or mixture Can form explosive gas-air mixtures.
- 5.3 Advice for firefighters
- · Protective equipment:

Do not inhale explosion gases or combustion gases.

Wear self-contained respiratory protective device.

· Additional information Cool endangered receptacles with water spray.





Printing date 25.02.2025 Version number 306 (replaces version 305) Revision: 25.02.2025

Trade name: One-Component Multi-Primer E-COLL

(Contd. of page 4)

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away. Ensure adequate ventilation

• 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Use only in well ventilated areas. Keep receptacles tightly sealed.

· Information about fire - and explosion protection:



Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Do not spray onto a naked flame or any incandescent material.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

· 7.2 Conditions for safe storage, including any incompatibilities

· Storage:

· Requirements to be met by storerooms and receptacles:

Store in a cool location.

Observe official regulations on storing packagings with pressurised containers.

- · Information about storage in one common storage facility: Store away from oxidising agents.
- · Further information about storage conditions: Protect from heat and direct sunlight.
- · 7.3 Specific end use(s) No further relevant information available.





Printing date 25.02.2025 Version number 306 (replaces version 305) Revision: 25.02.2025

Trade name: One-Component Multi-Primer E-COLL

(Contd. of page 5)

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

CAS: 115-10-6 dimethyl ether

IOELV Long-term value: 1920 mg/m³, 1000 ppm

CAS: 123-86-4 n-butyl acetate

IOELV Short-term value: 723 mg/m³, 150 ppm
Long-term value: 241 mg/m³, 50 ppm

CAS: 67-64-1 acetone

IOELV Long-term value: 1210 mg/m³, 500 ppm

CAS: 1330-20-7 Xylene

IOELV Short-term value: 442 mg/m³, 100 ppm

Long-term value: 221 mg/m³, 50 ppm

Skin

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see section 7.
- · Individual protection measures, such as personal protective equipment
- · General protective and hygienic measures:

Wash hands before breaks and at the end of work.

Avoid contact with the skin.

Avoid contact with the eyes.

Respiratory protection:

Not necessary if room is well-ventilated.

Use suitable respiratory protective device in case of insufficient ventilation.

Self-contained respiratory protective device.

· Hand protection



Protective gloves

Material of gloves

Butyl rubber, BR

Recommended thickness of the material: $\geq 0.4 \text{ mm}$

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 7)






Printing date 25.02.2025 Version number 306 (replaces version 305) Revision: 25.02.2025

Trade name: One-Component Multi-Primer E-COLL

(Contd. of page 6)

· Eye/face protection



· Body protection: Protective work clothing

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Colour: Grey

Odour: Characteristic
 Odour threshold: Not determined.
 Melting point/freezing point: Undetermined.

 \cdot Boiling point or initial boiling point and boiling

range Not applicable, as aerosol.

· Flammability Not applicable.

 \cdot Lower and upper explosion limit

• **Lower**: 1.2 Vol % • **Upper**: 18.6 Vol %

• Flash point: Not applicable, as aerosol.

· Auto-ignition temperature: 235 °C

Decomposition temperature: Not determined.pH Not determined.

· Viscosity:

· Kinematic viscosity Not determined.

Kinematic: 23 °C - 4 mm (ISO 2431)

• **Dynamic:** Not determined.

· Solubility

• water: Not miscible or difficult to mix.

Partition coefficient n-octanol/water (log value)
 Vapour pressure at 20 °C:
 4300 hPa

· Density and/or relative density

Density at 20 °C:

 Relative density
 Vapour density

 O.83 g/cm³

 Not determined.

 Not determined.
 Not determined.

· 9.2 Other information

· Appearance:

· Form: Aerosol

· Important information on protection of health

and environment, and on safety.

· **Ignition temperature:** Product is not selfigniting.

• Explosive properties: Not determined.

· Solvent separation test:

• Organic solvents: 84.0 % • VOC (EC) % 697,2 g/l

(Contd. on page 8)





Printing date 25.02.2025 Version number 306 (replaces version 305) Revision: 25.02.2025

Trade name: One-Component Multi-Primer E-COLL

(Contd. of page 7)

· VOC (EC) g/l

· VOCV (CH) 84,00 %

· Change in condition

· Drip point:

Oxidising propertiesEvaporation rateNot determined.Not applicable.

· Information with regard to physical hazard

classes

Explosives VoidFlammable gases Void

· Aerosols Extremely flammable aerosol. Pressurised container:

Void

May burst if heated.

 Oxidising gases Void · Gases under pressure Void · Flammable liquids Void · Flammable solids Void · Self-reactive substances and mixtures Void · Pyrophoric liquids Void · Pyrophoric solids Void · Self-heating substances and mixtures Void · Substances and mixtures, which emit flammable gases in contact with water Void · Oxidising liquids Void · Oxidising solids Void Void · Organic peroxides · Corrosive to metals Void

SECTION 10: Stability and reactivity

- 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability

· Desensitised explosives

· Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.





Printing date 25.02.2025 Version number 306 (replaces version 305) Revision: 25.02.2025

Trade name: One-Component Multi-Primer E-COLL

(Contd. of page 8)

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:				
CAS: 115-10-6 dimethyl ether				
Inhalative	Inhalative LC50/4h 308 ppm (rat)			
CAS: 123-86-4 n-butyl acetate				
Oral	LD50	13,100 mg/kg (rat)		
Dermal	LD50	>5,000 mg/kg (rabbit)		
Inhalative	LC50/4h	>21 ppm (rat)		
CAS: 67-64-1 acetone				
Oral	LD50	5,800 mg/kg (rat)		
Dermal	LD50	20,000 mg/kg (rabbit)		
Inhalative	LC50/4h	76 mg/m³ (rat)		
CAS: 1314-13-2 zinc oxide				
	LD50	>5,000 mg/kg (rat)		
CAS: 7779-90-0 trizinc bis(orthophosphate)				
Oral	LD50	>5,000 mg/kg (rat)		
CAS: 25068-38-6 reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700)				
Oral	LD50	11,400 mg/kg (rat)		
		22,800 mg/kg (rabbit) (GESTIS)		
CAS: 71-36-3 butan-1-ol				
Oral	LD50	790 mg/kg (rat)		
Dermal	LD50	3,400 mg/kg (rabbit)		
Inhalative	LC50/4h	8,000 ppm (rat)		

- · Primary irritant effect:
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation

Causes serious eye irritation.

· Respiratory or skin sensitisation

May cause an allergic skin reaction.

- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.

(Contd. on page 10)





Printing date 25.02.2025 Version number 306 (replaces version 305) Revision: 25.02.2025

Trade name: One-Component Multi-Primer E-COLL

(Contd. of page 9)

· STOT-single exposure

May cause drowsiness or dizziness.

- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.
- · 11.2 Information on other hazards
- · Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

· 12.1 Toxicity

12.1 Toxiony			
· Aquatic toxicity:			
CAS: 123-86-4 n-butyl acetate			
LC50 (96h)	18 mg/L (Pimephales promelas)		
EC50 (48h)	44 mg/L (Daphnia magna)		
EC50/24h	73 mg/l (Daphnia magna)		
EC50/72h	647.7 mg/l (S)		
CAS: 67-64-1 acetone			
LC50 (96h)	5,000 mg/L (Lepomis macrochirus)		
LC50/48h	8,800 mg/l (Daphnia magna)		
NOEC	430 mg/l (algae)		
NOEC/16h	1,700 mg/l (Pseudomonas putida)		
NOEC/48h	4,740 mg/l (Pseudokirchneriella subcapitata)		
96h LC50	5,540 mg/l (Oncorhynchus mykiss)		
CAS: 25068-38-6 reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average			
molecular weight ≤ 700)			
EC50 (48h)	2.8 mg/L (daphnia)		
96h LC50	3.6 mg/l (Leuciscus idus auratus)		

- · 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- \cdot 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

(Contd. on page 11)





Printing date 25.02.2025 Version number 306 (replaces version 305) Revision: 25.02.2025

Trade name: One-Component Multi-Primer E-COLL

(Contd. of page 10)

· 12.7 Other adverse effects

· Remark: Harmful to fish

- · Additional ecological information:
- · General notes:

Harmful to aquatic organisms

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods:

Containers can be recycled if completely empty; if not, dispose product/containers as dangerous waste. Observe local regulations.

· European waste catalogue

15 01 10* packaging containing residues of or contaminated by hazardous substances

SECTION 14: Transport information

· 14.1 UN number or ID number

· ADR, IMDG, IATA UN1950

· 14.2 UN proper shipping name

· **ADR** UN1950 AEROSOLS

· IMDG, IATA AEROSOLS

· 14.3 Transport hazard class(es)

· ADR





· Class 2 5F Gases.

· Label 2.1

·IMDG





· Class 2 Gases.

(Contd. on page 12)





Version number 306 (replaces version 305) Revision: 25.02.2025 Printing date 25.02.2025

Trade name: One-Component Multi-Primer E-COLL

(Contd. of page 11)

· Label 2.1

·IATA



· Class 2 Gases. · Label 2.1

· 14.4 Packing group

· ADR Void

· 14.5 Environmental hazards:

· Marine pollutant: Nο

Symbol (fish and tree) · Special marking (ADR): Symbol (fish and tree)

· 14.6 Special precautions for user Warning: Gases.

· EMS Number: F-D,S-U

14.7 Maritime transport in bulk according to IMO

instruments Not applicable.

· Transport/Additional information:

· ADR

· Limited quantities (LQ) 1L · Transport category 2 · Tunnel restriction code

· UN "Model Regulation": UN1950, AEROSOLS, 2.1

SECTION 15: Regulatory information

- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms







- · Signal word Danger
- · Hazard-determining components of labelling:

n-butyl acetate

reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700) (Contd. on page 13)





Printing date 25.02.2025 Version number 306 (replaces version 305) Revision: 25.02.2025

Trade name: One-Component Multi-Primer E-COLL

(Contd. of page 12)

acetone

butan-1-ol

Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H319 Causes serious eye irritation.
 H317 May cause an allergic skin reaction.
 H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P261 Avoid breathing spray.

P271 Use only outdoors or in a well-ventilated area.

P273 Avoid release to the environment.

P280 Wear protective gloves / eye protection / face protection.

P302+P352 IF ON SKIN: Wash with plenty of water.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P405 Store locked up.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· Chemical safety assessment

· Named dangerous substances - ANNEX I Methanol

- · Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- · DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment Annex II

None of the ingredients is listed.

- · REGULATION (EU) 2019/1148
- Annex I RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

· Annex II - REPORTABLE EXPLOSIVES PRECURSORS

CAS: 67-64-1 acetone

· Regulation (EC) No 273/2004 on drug precursors

CAS: 67-64-1 acetone

|3

 Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

CAS: 67-64-1 acetone

(Contd. on page 14)





Version number 306 (replaces version 305) Printing date 25.02.2025 Revision: 25.02.2025

Trade name: One-Component Multi-Primer E-COLL

(Contd. of page 13)

· Exposure scenario(s)

Exposure scenario(s) of ingredients (if present) are available on request at: sdb@ede.de

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

. Ralavant nhrasas

. IZCICVALI	· Nelevant pinases		
H220	Extremely flammable gas.		
H225	Highly flammable liquid and vapour.		
H226	Flammable liquid and vapour.		
H302	Harmful if swallowed.		
H304	May be fatal if swallowed and enters airways.		
H312	Harmful in contact with skin.		
H315	Causes skin irritation.		
H317	May cause an allergic skin reaction		

May cause an allergic skin reaction. H318 Causes serious eye damage.

H319 Causes serious eye irritation.

Harmful if inhaled. H332

H335 May cause respiratory irritation. May cause drowsiness or dizziness. H336

H373 May cause damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects. H411 Toxic to aquatic life with long lasting effects.

Harmful to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

EUH205 Contains epoxy constituents. May produce an allergic reaction.

Date of previous version: 07.12.2020

· Version number of previous version: 305

· Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOCV: Lenkungsabgabe auf flüchtigen organischen Verbindungen, Schweiz (Swiss Ordinance on volatile organic compounds)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Gas 1A: Flammable gases - Category 1A

Aerosol 1: Aerosols - Category 1

Flam. Liq. 2: Flammable liquids - Category 2 Flam. Liq. 3: Flammable liquids – Category 3 Acute Tox. 4: Acute toxicity - Category 4 Skin Irrit. 2: Skin corrosion/irritation - Category 2

Eye Dam. 1: Serious eye damage/eye irritation - Category 1 Eye Irrit. 2: Serious eye damage/eye irritation - Category 2

(Contd. on page 15)





Printing date 25.02.2025 Version number 306 (replaces version 305) Revision: 25.02.2025

Trade name: One-Component Multi-Primer E-COLL

(Contd. of page 14)

Skin Sens. 1: Skin sensitisation - Category 1

STOT SE 3: Specific target organ toxicity (single exposure) - Category 3 STOT RE 2: Specific target organ toxicity (repeated exposure) - Category 2

Asp. Tox. 1: Aspiration hazard – Category 1
Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1
Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

· * Data compared to the previous version altered.

EU —