

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 14.10.2024

Version number 301

Revision: 14.10.2024

* SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier** 600450
- **Trade name:** Rust primer, red-brown E-COLL
- **Article number:** 4317784305327, 4317784305303
- **UFI:** FHGQ-FARE-5A0V-Q7RP
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
 - **Sector of Use**
 - SU19 Building and construction work
 - SU21 Consumer uses: Private households / general public / consumers
 - SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
 - **Product category** PC9a Coatings and paints, thinners, paint removers
- **Application of the substance / the mixture** Anticorrosion additive
- **1.3 Details of the supplier of the safety data sheet**
 - **Manufacturer/Supplier:**
E/D/E - Einkaufsbuero Deutscher Eisenhaendler GmbH
EDE Platz 1
D-42389 Wuppertal
Germany

Tel. +49 202 6096-0
e-mail: sdb@ede.de
- **Further information obtainable from:** Product safety department
- **1.4 Emergency telephone number:**
Poison Control Center Mainz - 24 hour emergency service – phone: +49 (0) 6131/19240

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
 - **Classification according to Regulation (EC) No 1272/2008**

Flam. Liq. 3	H226	Flammable liquid and vapour.
STOT SE 3	H335-H336	May cause respiratory irritation. May cause drowsiness or dizziness.
Aquatic Chronic 2	H411	Toxic to aquatic life with long lasting effects.

· 2.2 Label elements

- **Labelling according to Regulation (EC) No 1272/2008**
The product is classified and labelled according to the CLP regulation.
- **Hazard pictograms**



GHS02 GHS07 GHS09

(Contd. on page 2)

EU

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 14.10.2024

Version number 301

Revision: 14.10.2024

Trade name: Rust primer, red-brown E-COLL

(Contd. of page 1)

Signal word Warning**Hazard-determining components of labelling:**

Hydrocarbons, C9, aromatics

Reaction mass of ethylbenzene and xylene

Hazard statements

H226 Flammable liquid and vapour.

H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P271 Use only outdoors or in a well-ventilated area.

P273 Avoid release to the environment.

P370+P378 In case of fire: Use CO₂, powder or water spray to extinguish.

P391 Collect spillage.

P403+P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking.

EUH208 Contains cobalt(II) 2-ethylhexanoate. May produce an allergic reaction.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Results of PBT and vPvB assessment**PBT:** Not applicable.**vPvB:** Not applicable.**SECTION 3: Composition/information on ingredients****3.2 Mixtures****Description:** Mixture of substances listed below with nonhazardous additions.**Dangerous components:**

CAS: 64742-95-6 EC number: 918-668-5 Index number: 649-356-00-4 Reg.nr.: 01-2119455851-35	Hydrocarbons, C9, aromatics Flam. Liq. 3, H226 Asp. Tox. 1, H304 Aquatic Chronic 2, H411 STOT SE 3, H335-H336 EUH066	>10-<20%
EC number: 905-588-0 Reg.nr.: 01-2119539452-40 02-2119752448216-32	Reaction mass of ethylbenzene and xylene Flam. Liq. 3, H226 STOT RE 2, H373; Asp. Tox. 1, H304 Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	2.5-10%

(Contd. on page 3)

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 14.10.2024

Version number 301

Revision: 14.10.2024

Trade name: Rust primer, red-brown E-COLL

(Contd. of page 2)

CAS: 1314-13-2 EINECS: 215-222-5 Index number: 030-013-00-7 Reg.nr.: 01-2119463881-32	zinc oxide ⚠ Aquatic Acute 1, H400; Aquatic Chronic 1, H410	>2.5-<5%
CAS: 7779-90-0 EINECS: 231-944-3 Index number: 030-011-00-6 Reg.nr.: 01-2119485044-40	trizinc bis(orthophosphate) ⚠ Aquatic Acute 1, H400; Aquatic Chronic 1, H410	>2.5-<5%
CAS: 13939-25-8 EINECS: 237-714-9	aluminium dihydrogen triphosphate ⚠ Eye Irrit. 2, H319	<1.25%
CAS: 136-52-7 EINECS: 205-250-6 Reg.nr.: 01-2119450011-60	cobalt(II) 2-ethylhexanoate ⚠ Repr. 1B, H360 ⚠ Aquatic Acute 1, H400 ⚠ Eye Irrit. 2, H319; Skin Sens. 1A, H317 Aquatic Chronic 3, H412	<0.1%
CAS: 34590-94-8 EINECS: 252-104-2 Reg.nr.: 01-2119450011-60-XXX	Dipropylene glycol monomethyl ether substance with a Community workplace exposure limit	<0.1%
Non-hazardous components		
CAS: 14807-96-6 EINECS: 238-877-9	Talc (Mg ₃ H ₂ (SiO ₃) ₄)	2.5-10%

- **Additional information:** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information:

Personal protection for the First Aider.
Immediately remove any clothing soiled by the product.

After inhalation:

Supply fresh air.
Seek medical treatment in case of complaints.
In case of unconsciousness place patient stably in side position for transportation.

After skin contact:

Immediately wash with water and soap and rinse thoroughly.
If skin irritation continues, consult a doctor.

After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

After swallowing:

Rinse out mouth and then drink plenty of water.
If symptoms persist consult doctor.

4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

(Contd. on page 4)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 14.10.2024

Version number 301

Revision: 14.10.2024

Trade name: Rust primer, red-brown E-COLL

(Contd. of page 3)

· 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures**· 5.1 Extinguishing media****· Suitable extinguishing agents:**CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.**· For safety reasons unsuitable extinguishing agents:** Water with full jet**· 5.2 Special hazards arising from the substance or mixture** No further relevant information available.**· 5.3 Advice for firefighters****· Protective equipment:** Do not inhale explosion gases or combustion gases.**SECTION 6: Accidental release measures****· 6.1 Personal precautions, protective equipment and emergency procedures**

Wear protective equipment. Keep unprotected persons away.

· 6.2 Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

Prevent seepage into sewage system, workpits and cellars.

Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage**· 7.1 Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace.**· Information about fire - and explosion protection:**

Keep ignition sources away - Do not smoke.

Protect from heat.

Protect against electrostatic charges.

(Contd. on page 5)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 14.10.2024

Version number 301

Revision: 14.10.2024

Trade name: Rust primer, red-brown E-COLL

(Contd. of page 4)

- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
Store only in the original receptacle.
Provide floor trough without outlet.
- **Information about storage in one common storage facility:** Store away from oxidising agents.
- **Further information about storage conditions:** Keep container tightly sealed.
- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

- **Ingredients with limit values that require monitoring at the workplace:**

CAS: 34590-94-8 Dipropylene glycol monomethyl ether

IOELV	Long-term value: 308 mg/m ³ , 50 ppm
	Skin

- **Additional information:** The lists valid during the making were used as basis.
- **8.2 Exposure controls**
- **Appropriate engineering controls** No further data; see section 7.
- **Individual protection measures, such as personal protective equipment**
- **General protective and hygienic measures:**
Avoid contact with the eyes and skin.
Wash hands before breaks and at the end of work.
Do not inhale gases / fumes / aerosols.
- **Respiratory protection:**
Use suitable respiratory protective device in case of insufficient ventilation - filter A2
- **Hand protection**



Protective gloves

- **Material of gloves**
Nitrile rubber, NBR
Penetration time (min.) : 480 min
Recommended thickness of the material: ≥ 0.4 mm

(Contd. on page 6)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 14.10.2024

Version number 301

Revision: 14.10.2024

Trade name: Rust primer, red-brown E-COLL

(Contd. of page 5)

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye/face protection Recommendation: safety glasses with side protection shield**· Body protection:** Use protective suit.**SECTION 9: Physical and chemical properties****· 9.1 Information on basic physical and chemical properties****· General Information**

· Colour:	Grey
· Odour:	Characteristic
· Odour threshold:	Not determined.
· Melting point/freezing point:	Undetermined.
· Boiling point or initial boiling point and boiling range	>100 °C
· Flammability	Not applicable.
· Lower and upper explosion limit	
· Lower:	Not determined.
· Upper:	Not determined.
· Flash point:	>23 °C
· Decomposition temperature:	Not determined.
· pH	Not determined.
· Viscosity:	
· Kinematic viscosity at 20 °C	200 s (DIN 53211/4)
· Kinematic: 23 °C - 4 mm (ISO 2431)	
· Dynamic:	Not determined.
· Solubility	
· water:	Not miscible or difficult to mix.
· Partition coefficient n-octanol/water (log value)	Not determined.
· Vapour pressure at 50 °C:	1,100 hPa
· Density and/or relative density	
· Density at 20 °C:	1.49 g/cm ³
· Relative density	Not determined.
· Vapour density	Not determined.

· 9.2 Other information**· Appearance:****· Form:**

Fluid

· Important information on protection of health and environment, and on safety.**· Ignition temperature:**

Product is not selfigniting.

· Explosive properties:

Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

· Solvent separation test:**· Organic solvents:**

34.0 %

· VOC (EC) g/l

430.0 g/l

· Change in condition**· Drip point:****· Oxidising properties**

Not determined.

(Contd. on page 7)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 14.10.2024

Version number 301

Revision: 14.10.2024

Trade name: Rust primer, red-brown E-COLL

(Contd. of page 6)

- Evaporation rate Not determined.
- Information with regard to physical hazard classes
 - Explosives Void
 - Flammable gases Void
 - Aerosols Void
 - Oxidising gases Void
 - Gases under pressure Void
 - Flammable liquids Flammable liquid and vapour.
 - Flammable solids Void
 - Self-reactive substances and mixtures Void
 - Pyrophoric liquids Void
 - Pyrophoric solids Void
 - Self-heating substances and mixtures Void
 - Substances and mixtures, which emit flammable gases in contact with water Void
 - Oxidising liquids Void
 - Oxidising solids Void
 - Organic peroxides Void
 - Corrosive to metals Void
 - Desensitised explosives Void

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** Reacts with acids, alkalis and oxidising agents.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** Carbon monoxide and carbon dioxide

SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Based on available data, the classification criteria are not met.

· **LD/LC50 values relevant for classification:**
CAS: 64742-95-6 Hydrocarbons, C9, aromatics

Oral LD50 >6,800 mg/kg (rat)

Dermal LD50 >3,400 mg/kg (rab)

Reaction mass of ethylbenzene and xylene

Oral LD50 4,300 mg/kg (rat)

(Contd. on page 8)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 14.10.2024

Version number 301

Revision: 14.10.2024

Trade name: Rust primer, red-brown E-COLL

(Contd. of page 7)

Dermal	LD50	2,000 mg/kg (rabbit)
CAS: 1314-13-2 zinc oxide		
Oral	LD50	>5,000 mg/kg (rat)
CAS: 7779-90-0 trizinc bis(orthophosphate)		
Oral	LD50	>5,000 mg/kg (rat)
CAS: 34590-94-8 Dipropylene glycol monomethyl ether		
Oral	LD50	5,135 mg/kg (rat)
Dermal	LD50	>19,000 mg/kg (rab)

- **Primary irritant effect:**
- **Skin corrosion/irritation** Based on available data, the classification criteria are not met.
- **Serious eye damage/irritation** Based on available data, the classification criteria are not met.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure**
May cause respiratory irritation. May cause drowsiness or dizziness.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.
- **11.2 Information on other hazards**

Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

(Contd. on page 9)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 14.10.2024

Version number 301

Revision: 14.10.2024

Trade name: Rust primer, red-brown E-COLL

(Contd. of page 8)

- **12.6 Endocrine disrupting properties** For information on endocrine disrupting properties see section 11.
- **12.7 Other adverse effects**
- **Remark:** Harmful to fish
- **Additional ecological information:**
- **General notes:**
Harmful to aquatic organisms
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods:**
Containers can be recycled if completely empty; if not, dispose product/containers as dangerous waste.
Observe local regulations.

· European waste catalogue	
08 01 11*	waste paint and varnish containing organic solvents or other dangerous substances

SECTION 14: Transport information

- **14.1 UN number or ID number**
· **ADR, IMDG, IATA** UN1263
- **14.2 UN proper shipping name**
· **ADR** UN1263 PAINT, ENVIRONMENTALLY HAZARDOUS
· **IMDG, IATA** PAINT
- **14.3 Transport hazard class(es)**

- **ADR**



- **Class** 3 (F1) Flammable liquids.
- **Label** 3

- **IMDG**



- **Class** 3 Flammable liquids.

(Contd. on page 10)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 14.10.2024

Version number 301

Revision: 14.10.2024

Trade name: Rust primer, red-brown E-COLL

(Contd. of page 9)

· Label

3

· IATA



· Class

3 Flammable liquids.

· Label

3

· 14.4 Packing group

· ADR, IMDG, IATA

III

· 14.5 Environmental hazards:

· Marine pollutant:

No

Symbol (fish and tree)

· Special marking (ADR):

Symbol (fish and tree)

· 14.6 Special precautions for user

Warning: Flammable liquids.

· Hazard identification number (Kemler code):

30

· EMS Number:

F-E, S-E

· Stowage Category

A

· 14.7 Maritime transport in bulk according to IMO instruments

Not applicable.

· Transport/Additional information:

· ADR

· Limited quantities (LQ)

5L

· Excepted quantities (EQ)

Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

· Transport category

3

· Tunnel restriction code

D/E

· IMDG

· Limited quantities (LQ)

5L

· Excepted quantities (EQ)

Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

· UN "Model Regulation":

UN 1263 PAINT, 3, III, ENVIRONMENTALLY
HAZARDOUS

SECTION 15: Regulatory information

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

· Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

(Contd. on page 11)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 14.10.2024

Version number 301

Revision: 14.10.2024

Trade name: Rust primer, red-brown E-COLL

(Contd. of page 10)

· Hazard pictograms

GHS02 GHS07 GHS09

· Signal word Warning**· Hazard-determining components of labelling:**

Hydrocarbons, C9, aromatics

Reaction mass of ethylbenzene and xylene

· Hazard statements

H226 Flammable liquid and vapour.

H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P271 Use only outdoors or in a well-ventilated area.

P273 Avoid release to the environment.

P370+P378 In case of fire: Use CO₂, powder or water spray to extinguish.

P391 Collect spillage.

P403+P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· Chemical safety assessment**· Qualifying quantity (tonnes) for the application of lower-tier requirements** 5,000 t**· Qualifying quantity (tonnes) for the application of upper-tier requirements** 50,000 t**· REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3**SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H360 May damage fertility or the unborn child.

H373 May cause damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

(Contd. on page 12)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 14.10.2024

Version number 301

Revision: 14.10.2024

Trade name: Rust primer, red-brown E-COLL

(Contd. of page 11)

H411 Toxic to aquatic life with long lasting effects.
H412 Harmful to aquatic life with long lasting effects.
EUH066 Repeated exposure may cause skin dryness or cracking.

· **Department issuing SDS:** Product safety department

· **Contact:** Head of Product Safety Department

· **Date of previous version:** 01.12.2020

· **Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity – Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1A: Skin sensitisation – Category 1A

Repr. 1B: Reproductive toxicity – Category 1B

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

· *** Data compared to the previous version altered.**