



Revision: 30.01.2025 Printing date 30.01.2025 Version number 308 (replaces version 307)

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier 600172
- · Trade name: High-performance cooling lubricant concentrate
- · Article number: 4317784348904, 4317784015356, 4317784564717, 4317784564724
- · UFI: 6R90-PG50-D20Q-12QU
- 1.2 Relevant identified uses of the substance or mixture and uses advised against
- · Sector of Use

SU21 Consumer uses: Private households / general public / consumers SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

- · Application of the substance / the mixture Coolant/ Cutting solution
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

E/D/E - Einkaufsbuero Deutscher Eisenhaendler GmbH EDE Platz 1 D-42389 Wuppertal Germany

Tel. +49 202 6096-0 e-mail: sdb@ede.de

- · Further information obtainable from: Product safety department
- · 1.4 Emergency telephone number:

Poison Control Center Mainz - 24 hour emergency service - phone: +49 (0) 6131/19240

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008

Eye Dam. 1 H318 Causes serious eye damage.

Skin Sens. 1 H317 May cause an allergic skin reaction.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- · 2.2 Label elements
- Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)





Printing date 30.01.2025 Version number 308 (replaces version 307) Revision: 30.01.2025

Trade name: High-performance cooling lubricant concentrate

(Contd. of page 1)

· Hazard pictograms





GHS05 GHS07

Signal word Danger

· Hazard-determining components of labelling:

2-Amino-2-ethyl-1,3-propanediol polysulfides, di-tert-dodecyl Amides, C12-18 and C18-unsatd., N-(hydroxyethyl), ethoxylated 1,2-benzisothiazol-3(2H)-one

· Hazard statements

H318 Causes serious eye damage.

H317 May cause an allergic skin reaction.

H412 Harmful to aquatic life with long lasting effects.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P273 Avoid release to the environment.

P280 Wear protective gloves / eye protection / face protection.

P302+P352 IF ON SKIN: Wash with plenty of water.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P321 Specific treatment (see on this label).

P362+P364 Take off contaminated clothing and wash it before reuse. P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· Additional information:

Use biocidal products with care. Always read the label and product information before use. Contains biocidal products: pyridine-2-thiol 1-oxide, sodium salt

· 2.3 Other hazards

· Results of PBT and vPvB assessment

· PBT: Not applicable.

· vPvB: Not applicable.





Printing date 30.01.2025 Version number 308 (replaces version 307) Revision: 30.01.2025

Trade name: High-performance cooling lubricant concentrate

(Contd. of page 2)

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:				
CAS: 64742-53-6 EINECS: 265-156-6 Index number: 649-466-00-2 Reg.nr.: 01-2119480375-34	baseoil - unspecified Asp. Tox. 1, H304	50-100%		
CAS: 68920-66-1 Reg.nr.: 01-2119489407-26	Fettalkohol, ethoxyliert Aquatic Chronic 2, H411 Skin Irrit. 2, H315	2.5-10%		
CAS: 115-70-8 Reg.nr.: 01-2119958191-37	2-Amino-2-ethyl-1,3-propanediol Eye Dam. 1, H318	>1-<2.5%		
CAS: 112-34-5 EINECS: 203-961-6 Index number: 603-096-00-8 Reg.nr.: 01-2119475104-44-0000	2-(2-butoxyethoxy)ethanol Eye Irrit. 2, H319	>0-<2.5%		
CAS: 157707-44-3 Polymer	Amides, C12-18 and C18-unsatd., N-(hydroxyethyl), ethoxylated Eye Dam. 1, H318	>1-<2.5%		
CAS: 68425-15-0 EINECS: 270-335-7	polysulfides, di-tert-dodecyl Skin Sens. 1B, H317	>1-<2.5%		
CAS: 2634-33-5 EINECS: 220-120-9 Index number: 613-088-00-6	1,2-benzisothiazol-3(2H)-one Acute Tox. 2, H330 Eye Dam. 1, H318 Aquatic Acute 1, H400; Aquatic Chronic 1, H410 Acute Tox. 4, H302; Skin Irrit. 2, H315; Skin Sens. 1A, H317 ATE: LD50 oral: 450 mg/kg LC50/4h inhalative: 0.21 ppm Specific concentration limit: Skin Sens. 1A; H317: C ≥ 0.036	<0.1%		
CAS: 3811-73-2 EINECS: 223-296-5	Pyrithione sodium (INNM) Acute Tox. 3, H311; Acute Tox. 3, H331 STOT RE 1, H372 Aquatic Acute 1, H400 (M=100); Aquatic Chronic 2, H411 Acute Tox. 4, H302; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	<0.1%		

· Additional information: For the wording of the listed hazard phrases refer to section 16.





Printing date 30.01.2025 Version number 308 (replaces version 307) Revision: 30.01.2025

Trade name: High-performance cooling lubricant concentrate

(Contd. of page 3)

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information: Personal protection for the First Aider.
- · After inhalation:

Supply fresh air.

Seek medical treatment in case of complaints.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly. If skin irritation continues, consult a doctor.

- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing:

Rinse out mouth and then drink plenty of water.

Do not induce vomiting; call for medical help immediately.

· 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

· 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- Suitable extinguishing agents: CO2, powder or water spray. Fight larger fire with alcohol resistant foam.
- · 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters
- **Protective equipment:** Wear self-contained respiratory protective device.

SECTION 6: Accidental release measures

- · 6.1 Personal precautions, protective equipment and emergency procedures Not required.
- · 6.2 Environmental precautions: No special measures required.
- · 6.3 Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

(Contd. on page 5)





Printing date 30.01.2025 Version number 308 (replaces version 307) Revision: 30.01.2025

Trade name: High-performance cooling lubricant concentrate

(Contd. of page 4)

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

- 7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.
- · Information about fire and explosion protection: No special measures required.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Store in a cool and dry place.

Store in a cool location.

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Store receptacle in a well ventilated area.
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Contr	· 8.1 Control parameters				
· Ingredien	· Ingredients with limit values that require monitoring at the workplace:				
CAS: 112-34-5 2-(2-butoxyethoxy)ethanol					
IOELV Short-term value: 101.2 mg/m³, 15 ppm Long-term value: 67.5 mg/m³, 10 ppm					
· DNELs	· DNELs				
CAS: 68920-66-1 Fettalkohol, ethoxyliert					
Dermal	DNEL (worker)	2,080 mg/kg bw/day (professional use)			
Inhalative	Long term value for employees	294 mg/m³ (professional use)			
CAS: 112-34-5 2-(2-butoxyethoxy)ethanol					
Oral	DNEL (populution)	1.25 mg/kg bw/day (cus)			
Dermal	DNEL (worker)	20 mg/kg bw/day (professional use)			
	DNEL (population)	10 mg/kg bw/day (cus)			
Inhalative	Long term value for employees	34 mg/m³ (cus)			
		67.5 mg/m³ (professional use)			
	DNEL (worker)	67.5 mg/m³ (professional use)			
	DNEL (population)	34 mg/m³ (cus)			
		(Contd. on page 6)			

(Contd. on page 6)





Printing date 30.01.2025 Version number 308 (replaces version 307) Revision: 30.01.2025

Trade name: High-performance cooling lubricant concentrate

(Contd. of page 5)

· PNECs

CAS: 112-34-5 2-(2-butoxyethoxy)ethanol

PNEC-Aquatic compartment Water 0.1 mg/L (Sea Water)

PNEC-Sewage treatment plant 200 mg/L (S)

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see section 7.
- · Individual protection measures, such as personal protective equipment

· General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed. Wash hands before breaks and at the end of work. Do not inhale gases / fumes / aerosols. Avoid contact with the eyes and skin.

· Hand protection



Protective gloves

· Material of gloves

Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.4 mm

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye/face protection



Tightly sealed goggles

· Body protection: Protective work clothing

SECTION 9: Physical and chemical properties

- \cdot 9.1 Information on basic physical and chemical properties
- · General Information

· Colour:

According to product specification

· Odour:

Characteristic

· Odour threshold:

Not determined.

(Contd. on page 7)





Revision: 30.01.2025 Printing date 30.01.2025 Version number 308 (replaces version 307)

Trade name: High-performance cooling lubricant concentrate

(Contd. of page 6)

· Melting point/freezing point: Undetermined.

· Boiling point or initial boiling point and boiling

Undetermined. range · Flammability Not applicable.

· Lower and upper explosion limit

· Lower: Not determined. · Upper: Not determined. · Flash point: Not applicable. · Decomposition temperature: Not determined.

· pH at 20 °C

· Viscosity:

· Kinematic viscosity at 40 °C 45 mm²/s

· Kinematic: 23 °C - 4 mm (ISO 2431)

· Dynamic: Not determined.

· Solubility

· water: Not miscible or difficult to mix.

· Partition coefficient n-octanol/water (log value) Not determined.

0.1 hPa · Vapour pressure at 20 °C:

· Density and/or relative density

· Density: Not determined. · Relative density Not determined. · Vapour density Not determined.

· 9.2 Other information

· Appearance:

· Form: Fluid

· Important information on protection of health and environment, and on safety.

· Ignition temperature: Product is not selfigniting.

· Explosive properties: Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

Void

Solvent separation test:

· VOC (EC) % 1-1.52 % · VOC (EC) g/l 9.1-13.9 g/l

· Change in condition

· Pyrophoric solids

· Drip point:

· Oxidising properties Not determined. · Evaporation rate Not determined.

· Information with regard to physical hazard classes

· Explosives Void · Flammable gases Void · Aerosols Void · Oxidising gases Void · Gases under pressure Void · Flammable liquids Void · Flammable solids Void · Self-reactive substances and mixtures Void · Pyrophoric liquids Void

(Contd. on page 8)





Printing date 30.01.2025 Version number 308 (replaces version 307) Revision: 30.01.2025

Trade name: High-performance cooling lubricant concentrate

(Contd. of page 7)

· Self-heating substances and mixtures	Void
 Substances and mixtures, which emit flammable 	•
gases in contact with water	Void
· Oxidising liquids	Void
· Oxidising solids	Void
· Organic peroxides	Void
· Corrosive to metals	Void
· Desensitised explosives	Void

SECTION 10: Stability and reactivity

- 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 v	· LD/LC50 values relevant for classification:		
CAS: 6474	CAS: 64742-53-6 baseoil - unspecified		
Oral	LD50	5,000 mg/kg (rat)	
Dermal	LD50	5,000 mg/kg (rat)	
CAS: 6892	CAS: 68920-66-1 Fettalkohol, ethoxyliert		
Oral	LD50	>2,000 mg/kg (rat)	
Dermal	LD50	>2,000 mg/kg (rabbit)	
Inhalative	LC50/6h	>100 mg/m³ (rat)	
CAS: 112-	CAS: 112-34-5 2-(2-butoxyethoxy)ethanol		
Oral	LD50	4,900 mg/kg (rat)	
Dermal	LD50	4,900 mg/kg (rabbit)	
CAS: 2634	CAS: 2634-33-5 1,2-benzisothiazol-3(2H)-one		
Oral	LD50	450 mg/kg (ATE)	
Inhalative	LC50/4h	0.21 ppm (ATE)	

(Contd. on page 9)





Printing date 30.01.2025 Version number 308 (replaces version 307) Revision: 30.01.2025

Trade name: High-performance cooling lubricant concentrate

(Contd. of page 8)

- · Primary irritant effect:
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation Causes serious eye damage.
- · Respiratory or skin sensitisation May cause an allergic skin reaction.
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.
- · 11.2 Information on other hazards
- · Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic to	· Aquatic toxicity:			
CAS: 647	CAS: 64742-53-6 baseoil - unspecified			
	EC50 (21d)	10 mg/L (Daphnia magna)		
	EC50 (48h)	>5,000 mg/L (Daphnia magna)		
	NOEC (21d)	10 mg/l (Daphnia magna)		
CAS: 6892	CAS: 68920-66-1 Fettalkohol, ethoxyliert			
	LC50 (96h)	108 mg/L (Brachydanio rerio)		
	EL50 akut (48h)	51 mg/l (Daphnia magna)		
	EL50 akut (72h)	>100 mg/l (Desmodesmus subspicatus)		
	NOEC (10d)	0.16 mg/l (Lepomis macrochirus)		
CAS: 112-	CAS: 112-34-5 2-(2-butoxyethoxy)ethanol			
Inhalative	LC50	>100 mg/L (crustacean)		
	LC50 akut (96h)	1,300 mg/L (Lepomis macrochirus)		
	LC50 akut	>100 mg/L (Brachydanio rerio)		
	EC50	>100 mg/l (Desmodesmus subspicatus)		

- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.

(Contd. on page 10)





Printing date 30.01.2025 Version number 308 (replaces version 307) Revision: 30.01.2025

Trade name: High-performance cooling lubricant concentrate

(Contd. of page 9)

- 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

- · 12.7 Other adverse effects
- · Additional ecological information:
- · General notes: Not hazardous for water.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods:

Containers can be recycled if completely empty; if not, dispose product/containers as dangerous waste. Observe local regulations.

SECTION 14: Transport information

· 14.1 UN number or ID number

· ADR, IMDG, IATA Void

· 14.2 UN proper shipping name

· ADR, IMDG, IATA Void

· 14.3 Transport hazard class(es)

· ADR, ADN, IMDG, IATA

· Class Void

· 14.4 Packing group

· ADR, IMDG, IATA Void

• 14.5 Environmental hazards: Not applicable.

• 14.6 Special precautions for user Not applicable.

· 14.7 Maritime transport in bulk according to IMO

instruments Not applicable.

· UN "Model Regulation": Void

EU -





Printing date 30.01.2025 Version number 308 (replaces version 307) Revision: 30.01.2025

Trade name: High-performance cooling lubricant concentrate

(Contd. of page 10)

SECTION 15: Regulatory information

- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms





GHS05 GHS07

- · Signal word Danger
- · Hazard-determining components of labelling:

2-Amino-2-ethyl-1,3-propanediol

polysulfides, di-tert-dodecyl

Amides, C12-18 and C18-unsatd., N-(hydroxyethyl), ethoxylated

1,2-benzisothiazol-3(2H)-one

· Hazard statements

H318 Causes serious eye damage.

H317 May cause an allergic skin reaction.

H412 Harmful to aquatic life with long lasting effects.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P273 Avoid release to the environment.

P280 Wear protective gloves / eye protection / face protection.

P302+P352 IF ON SKIN: Wash with plenty of water.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P321 Specific treatment (see on this label).

P362+P364 Take off contaminated clothing and wash it before reuse.
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- · DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment Annex II

None of the ingredients is listed.

- · REGULATION (EU) 2019/1148
- · Annex I RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

(Contd. on page 12)





Printing date 30.01.2025 Version number 308 (replaces version 307) Revision: 30.01.2025

Trade name: High-performance cooling lubricant concentrate

(Contd. of page 11)

· Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

 Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

- National regulations:
- · Verordnung (EU) Nr. 528/2012 Verwendung von Biozidprodukten applicable

· Information about limitation of use:

Employment restrictions concerning pregnant and lactating women must be observed.

· Exposure scenario(s)

Exposure scenario(s) of ingredients (if present) are available on request at: sdb@ede.de

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H311 Toxic in contact with skin.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H330 Fatal if inhaled.

H331 Toxic if inhaled.

H372 Causes damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

· Contact: sdb@ede.de

Date of previous version: 18.10.2021
Version number of previous version: 307

· Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU) DNEL: Derived No-Effect Level (REACH)

(Contd. on page 13)





Printing date 30.01.2025 Version number 308 (replaces version 307) Revision: 30.01.2025

Trade name: High-performance cooling lubricant concentrate

(Contd. of page 12)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative

ATE: Acute toxicity estimate values Acute Tox. 4: Acute toxicity - Category 4

Acute Tox. 3: Acute toxicity - Category 3

Acute Tox. 2: Acute toxicity - Category 2 Skin Irrit. 2: Skin corrosion/irritation - Category 2

Eye Dam. 1: Serious eye damage/eye irritation - Category 1 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation - Category 1 Skin Sens. 1A: Skin sensitisation – Category 1A Skin Sens. 1B: Skin sensitisation – Category 1B

STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1 Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1 Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard — Category 1 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard — Category 2 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

· * Data compared to the previous version altered.

EU -