

Printing date 05.11.2024 Version number 306 (replaces version 305) Revision: 05.11.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier 600026

· Trade name: Concentrated drilling oil E-COLL

· Article number: 4317784015530, 4317784015547, 4317784348874

· **UFI**: TR10-90JY-W00A-2543

1.2 Relevant identified uses of the substance or mixture and uses advised against

· Sector of Use

SU21 Consumer uses: Private households / general public / consumers

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

- · Product category PC8 Biocidal products
- · Application of the substance / the mixture Coolant/ Cutting solution
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

E/D/E - Einkaufsbuero Deutscher Eisenhaendler GmbH EDE Platz 1 D-42389 Wuppertal Germany

Tel. +49 202 6096-0 e-mail: sdb@ede.de

- · Further information obtainable from: Product safety department
- · 1.4 Emergency telephone number:

Poison Control Center Mainz - 24 hour emergency service - phone: +49 (0) 6131/19240

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008

Eye Irrit. 2 H319 Causes serious eye irritation.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- · 2.2 Label elements
- Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms



· Signal word Warning



Printing date 05.11.2024 Version number 306 (replaces version 305) Revision: 05.11.2024

Trade name: Concentrated drilling oil E-COLL

(Contd. of page 1)

· Hazard statements

H319 Causes serious eve irritation.

H412 Harmful to aquatic life with long lasting effects.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.
P264 Wash thoroughly after handling.
P273 Avoid release to the environment.
P280 Wear eye protection / face protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P337+P313 If eye irritation persists: Get medical advice/attention.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· Additional information:

Use biocidal products with care. Always read the label and product information before use. EUH208 Contains 1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction. Contains biocidal products: pyridine-2-thiol 1-oxide, sodium salt, 1,2-benzisothiazol-3(2H)-one

· 2.3 Other hazards

· Results of PBT and vPvB assessment

PBT: Not applicable.vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
CAS: 64742-53-6 EINECS: 265-156-6 Index number: 649-466-00-2 Reg.nr.: 01-2119480375-34-xxxx	Distillates (petroleum), hydrotreated light naphthenic	50-100%
CAS: 64742-54-7 EINECS: 265-157-1 Index number: 649-467-00-8 Reg.nr.: 01-211948627-25-xxxx 01-2119471299-27	Distillates (petroleum), hydrotreated heavy paraffinic ♣ Asp. Tox. 1, H304 Specific concentration limit: Asp. Tox. 1; H304: C ≥ 5 %	10-50%
CAS: 68920-66-1 Reg.nr.: 01-2119489407-26	Fettalkohol, ethoxyliert Aquatic Chronic 2, H411 Skin Irrit. 2, H315	2.5-10%
CAS: 64742-54-7 EINECS: 265-157-1 Index number: 649-467-00-8 Reg.nr.: 01-2119484627-25-0025	Distillates (petroleum), hydrotreated heavy paraffinic Asp. Tox. 1, H304	<1.25%
CAS: 157707-44-3 Polymer	Amides, C12-18 and C18-unsatd., N-(hydroxyethyl), ethoxylated Eye Dam. 1, H318	<1.25%

(Contd. on page 3)



Printing date 05.11.2024 Version number 306 (replaces version 305) Revision: 05.11.2024

Trade name: Concentrated drilling oil E-COLL

	(Con	itd. of page 2)
CAS: 3811-73-2 EINECS: 223-296-5 Index number: 613-344-00-7	pyridine-2-thiol 1-oxide, sodium salt STOT RE 1, H372 Aquatic Acute 1, H400 (M=100); Aquatic Chronic 1, H410 (M=1) Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317 ATE: LD50 oral: 500 mg/kg LD50 dermal: 790 mg/kg LC50/4h inhalative: 0.5 ppm	<0.1%
CAS: 2634-33-5 EINECS: 220-120-9 Index number: 613-088-00-6	1,2-benzisothiazol-3(2H)-one Acute Tox. 2, H330 Eye Dam. 1, H318 Aquatic Acute 1, H400; Aquatic Chronic 1, H410 Acute Tox. 4, H302; Skin Irrit. 2, H315; Skin Sens. 1A, H317 ATE: LD50 oral: 450 mg/kg LC50/4h inhalative: 0.21 ppm Specific concentration limit: Skin Sens. 1A; H317: C ≥ 0.036	<0.1%

· Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

· General information:

Personal protection for the First Aider. Immediately remove any clothing soiled by the product.

· After inhalation:

Supply fresh air.

Seek medical treatment in case of complaints.

· After skin contact: If skin irritation continues, consult a doctor.

· After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· After swallowing:

Rinse out mouth and then drink plenty of water.

Do not induce vomiting; call for medical help immediately.

- · 4.2 Most important symptoms and effects, both acute and delayed Gastric or intestinal disorders
- 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.



Printing date 05.11.2024 Version number 306 (replaces version 305) Revision: 05.11.2024

Trade name: Concentrated drilling oil E-COLL

(Contd. of page 3)

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents: CO2, powder or water spray. Fight larger fire with alcohol resistant foam.
- · 5.2 Special hazards arising from the substance or mixture

In case of fire, the following can be released:

Nitrogen oxides (NOx)

Carbon monoxide (CO)

Under certain fire conditions, traces of other toxic gases cannot be excluded.

- · 5.3 Advice for firefighters
- · Protective equipment: Wear self-contained respiratory protective device.
- · Additional information

Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures

 \cdot 6.1 Personal precautions, protective equipment and emergency procedures

Particular danger of slipping on leaked/spilled product.

- 6.2 Environmental precautions: No special measures required.
- · 6.3 Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

- 7.1 Precautions for safe handling Store in cool, dry place in tightly closed receptacles.
- · Information about fire and explosion protection:

Protect from heat.

Avoid open flames, sparks, other sources of ignition and direct sunlight.

· 7.2 Conditions for safe storage, including any incompatibilities

Keep food, beverages and pet food away.

- · Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.

(Contd. on page 5)



Printing date 05.11.2024 Version number 306 (replaces version 305) Revision: 05.11.2024

Trade name: Concentrated drilling oil E-COLL

(Contd. of page 4)

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep container tightly sealed. Protect from contamination.

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · 8.1 Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

mornio da da mornio de la mornio della morni					
· DNELs					
CAS: 6474	CAS: 64742-54-7 Distillates (petroleum), hydrotreated heavy paraffinic				
Inhalative	DNEL (worker)	5.6 mg/m³ (professional use)			
	DNEL (population)	1.2 mg/m³ (cus)			
CAS: 6892	CAS: 68920-66-1 Fettalkohol, ethoxyliert				
Dermal	DNEL (worker)	2,080 mg/kg bw/day (professional use)			
Inhalative	Long term value for employees	294 mg/m³ (professional use)			
CAS: 64742-54-7 Distillates (petroleum), hydrotreated heavy paraffinic					
Inhalative	Long term value for employees	5.4 mg/m³ (rat)			

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see section 7.
- · Individual protection measures, such as personal protective equipment
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

Respiratory protection:

Respiratory protection is not required when used properly and under normal conditions.

Filter P2

FFP₂

Respiratory protective devices - gas filters and combination devices according to DIN EN 141

· Hand protection





Printing date 05.11.2024 Version number 306 (replaces version 305) Revision: 05.11.2024

Trade name: Concentrated drilling oil E-COLL

(Contd. of page 5)

Only use chemical-protective gloves with CE-labelling of category III.

· Material of gloves

Nitrile rubber, NBR Chloroprene rubber, CR Penetration time (min.) : > 480

Recommended thickness of the material: ≥ 0.4 mm

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

The determined penetration times according to EN 16523-1:2015 are not performed under practical conditions. Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended.

· Eye/face protection



Tightly sealed goggles

Recommendation: safety glasses with side protection shield

· Body protection:

Protective work clothing Impervious protective clothing

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

Colour:
 Odour:
 Odour threshold:
 Melting point/freezing point:
 Orange
 Characteristic
 Not determined.
 Undetermined.

· Boiling point or initial boiling point and boiling

range >270 °C • Flammability Not applicable.

· Lower and upper explosion limit

Lower: Not determined.
 Upper: Not determined.

· Flash point: 101 °C

Decomposition temperature: Not determined.pH Not determined.

· Viscosity:

Kinematic viscosity at 40 °C
 30 mm²/s

Kinematic: 23 °C - 4 mm (ISO 2431)

• Dynamic at 40 °C: 27 mPas

Solubility

water: Fully miscible.
Partition coefficient n-octanol/water (log value)
Not determined.

· Vapour pressure at 20 °C: 0.1 hPa

Density and/or relative density

• **Density at 20 °C:** 0.89 g/cm³

(Contd. on page 7)



Printing date 05.11.2024 Version number 306 (replaces version 305) Revision: 05.11.2024

Trade name: Concentrated drilling oil E-COLL

(Contd. of page 6)

Relative densityVapour densityNot determined.Not determined.

· 9.2 Other information

· Appearance:

· Form: Fluid

· Important information on protection of health and environment, and on safety.

· **Ignition temperature:** Product is not selfigniting.

• Explosive properties: Product does not present an explosion hazard.

· Solvent separation test:

· VOC (EC) %
 · VOC (EC) g/I
 · Solids content:
 0.0 %

 $\cdot \ \, \text{Change in condition}$

· Drip point:

Oxidising propertiesEvaporation rateNot determined.Not determined.

· Information with regard to physical hazard

classes

· Explosives Void Flammable gases Void · Aerosols Void · Oxidising gases Void Void · Gases under pressure · Flammable liquids Void · Flammable solids Void · Self-reactive substances and mixtures Void Pyrophoric liquids Void Pyrophoric solids Void · Self-heating substances and mixtures Void · Substances and mixtures, which emit flammable gases in contact with water Void · Oxidising liquids Void · Oxidising solids Void · Organic peroxides Void · Corrosive to metals Void · Desensitised explosives Void

SECTION 10: Stability and reactivity

- 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.

(Contd. on page 8)



Printing date 05.11.2024 Version number 306 (replaces version 305) Revision: 05.11.2024

Trade name: Concentrated drilling oil E-COLL

(Contd. of page 7)

- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 v	LD/LC50 values relevant for classification:		
CAS: 64742-53-6 Distillates (petroleum), hydrotreated light naphthenic			
Oral	LD50	5,000 mg/kg (rat)	
Dermal	LD50	5,000 mg/kg (rat)	
CAS: 6474	CAS: 64742-54-7 Distillates (petroleum), hydrotreated heavy paraffinic		
Oral	LD50	>2,000 mg/kg (rat) (OCED 401)	
Dermal	LD50	>2,000 mg/kg (rabbit) (OCED 402)	
	NOEC(14d)	≥1,000 mg/l (Fis)	
CAS: 6892	CAS: 68920-66-1 Fettalkohol, ethoxyliert		
Oral	LD50	>2,000 mg/kg (rat)	
Dermal	LD50	>2,000 mg/kg (rabbit)	
Inhalative	LC50/6h	>100 mg/m³ (rat)	
CAS: 6474	CAS: 64742-54-7 Distillates (petroleum), hydrotreated heavy paraffinic		
Inhalative	LC50/4h	>100 mg/m³ (Pimephales promelas)	
CAS: 381	CAS: 3811-73-2 pyridine-2-thiol 1-oxide, sodium salt		
Oral	LD50	500 mg/kg (ATE)	
		500 mg/kg (rat)	
Dermal	LD50	790 mg/kg (ATE)	
		1,100 mg/kg (rat)	
Inhalative	LC50/4h	0.5 ppm (ATE)	
		1.5 ppm (rat)	
CAS: 2634-33-5 1,2-benzisothiazol-3(2H)-one			
Oral	LD50	450 mg/kg (ATE)	
Inhalative	LC50/4h	0.21 ppm (ATE)	

- · Primary irritant effect:
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation Causes serious eye irritation.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.

(Contd. on page 9)



Printing date 05.11.2024 Version number 306 (replaces version 305) Revision: 05.11.2024

Trade name: Concentrated drilling oil E-COLL

(Contd. of page 8)

- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.
- · 11.2 Information on other hazards
- · Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity:		
CAS: 64742-53-6 Distillates (petroleum), hydrotreated light naphthenic		
EC50 (21d)	>10 mg/L (Daphnia galeata)	
EC50 (48h)	>10,000 mg/L (Daphnia galeata)	
NOEC (21d)	10 mg/l (Daphnia galeata)	
CAS: 64742-54-7 Distillates (petroleum), hydrotreated heavy paraffinic		
LC50 (96h)	>100 mg/L (Pimephales promelas) (OCED 203)	
EC50 (48h)	>10,000 mg/L (Daphnia magna) (OECD 202)	
CAS: 68920-66-1 Fettalkohol, ethoxyliert		
LC50 (96h)	108 mg/L (Brachydanio rerio)	
EL50 akut (48h)	51 mg/l (Daphnia magna)	
EL50 akut (72h)	>100 mg/l (Desmodesmus subspicatus)	
NOEC (10d)	0.16 mg/l (Lepomis macrochirus)	
CAS: 64742-54-7 Distillates (petroleum), hydrotreated heavy paraffinic		
LC50 (96h)	>100 mg/L (Pimephales promelas)	
EC50 (21d)	>10 mg/L (Daphnia galeata)	
EC50 (48h)	>10,000 mg/L (Daphnia galeata)	
EC50/72h	>100 mg/l (Desmodesmus subspicatus)	
EL50/48h	>100 mg/l (Pseudokirchneriella subcapitata)	
	>10,000 mg/l (Daphnia magna)	
NOEC (21d)	>10 mg/l (Daphnia galeata)	

- · 12.2 Persistence and degradability No further relevant information available.
- \cdot 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.



Printing date 05.11.2024 Version number 306 (replaces version 305) Revision: 05.11.2024

Trade name: Concentrated drilling oil E-COLL

(Contd. of page 9)

· 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

- · 12.7 Other adverse effects
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Harmful to aquatic organisms

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods:

Containers can be recycled if completely empty; if not, dispose product/containers as dangerous waste. Observe local regulations.

- · European waste catalogue
- · Recommended cleansing agents: Water, if necessary together with cleansing agents.

SECTION 14: Transport information

· 14.1 UN number or ID number

· ADR, IMDG, IATA Void

· 14.2 UN proper shipping name

· ADR, IMDG, IATA Void

· 14.3 Transport hazard class(es)

· ADR, ADN, IMDG, IATA

· Class Void

· 14.4 Packing group

· ADR, IMDG, IATA Void

• 14.5 Environmental hazards: Not applicable.

• 14.6 Special precautions for user Not applicable.

14.7 Maritime transport in bulk according to IMO

instruments Not applicable.

· UN "Model Regulation": Void

SECTION 15: Regulatory information

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.



Printing date 05.11.2024 Version number 306 (replaces version 305) Revision: 05.11.2024

Trade name: Concentrated drilling oil E-COLL

(Contd. of page 10)

- · Labelling according to Regulation (EC) No 1272/2008
- The product is classified and labelled according to the CLP regulation.
- · Hazard pictograms



- · Signal word Warning
- · Hazard statements

H319 Causes serious eye irritation.

H412 Harmful to aquatic life with long lasting effects.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.
P264 Wash thoroughly after handling.
P273 Avoid release to the environment.
P280 Wear eye protection / face protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P337+P313 If eye irritation persists: Get medical advice/attention.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- · DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment Annex II

None of the ingredients is listed.

- · REGULATION (EU) 2019/1148
- · Annex I RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

· Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

· Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

- · National regulations:
- · Verordnung (EU) Nr. 528/2012 Verwendung von Biozidprodukten applicable
- · Information about limitation of use:

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.

Employment restrictions concerning pregnant and lactating women must be observed.



Printing date 05.11.2024 Version number 306 (replaces version 305) Revision: 05.11.2024

Trade name: Concentrated drilling oil E-COLL

(Contd. of page 11)

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H330 Fatal if inhaled.

H332 Harmful if inhaled.

H372 Causes damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

· Contact: sdb@ede.de

 Date of previous version: 20.11.2023 Version number of previous version: 305

Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the

International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU) DNEL: Derived No-Effect Level (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

ATE: Acute toxicity estimate values

Acute Tox. 4: Acute toxicity – Category 4 Acute Tox. 2: Acute toxicity – Category 2

Skin Irrit. 2: Skin corrosion/irritation - Category 2

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

Eye Irrit. 2: Serious eye damage/eye irritation - Category 2

Skin Sens. 1: Skin sensitisation - Category 1

Skin Sens. 1A: Skin sensitisation - Category 1A

STOT RE 1: Specific target organ toxicity (repeated exposure) - Category 1

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

· * Data compared to the previous version altered.