

Printing date 24.09.2024 Version number 308 (replaces version 307) Revision: 24.09.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier 600090

· Trade name: Jump start spray E-COLL

· Article number: 4317784409346

· UFI: PMER-AXM9-SC0W-SFK5

1.2 Relevant identified uses of the substance or mixture and uses advised against

· Sector of Use

SU21 Consumer uses: Private households / general public / consumers

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

- · Application of the substance / the mixture Water displacing agent
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

E/D/E - Einkaufsbuero Deutscher Eisenhaendler GmbH EDE Platz 1 D-42389 Wuppertal Germany

Tel. +49 202 6096-0 e-mail: sdb@ede.de

- · Further information obtainable from: Product safety department
- · 1.4 Emergency telephone number:

Poison Control Center Mainz - 24 hour emergency service - phone: +49 (0) 6131/19240

SECTION 2: Hazards identification

· 2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Aerosol 1	H222-H229	Extremely flammable aerosol. Pressurised container: May burst if heated.
Skin Irrit. 2	H315	Causes skin irritation.
Eye Irrit. 2	H319	Causes serious eye irritation.
STOT SE 3	H336	May cause drowsiness or dizziness.
Asp. Tox. 1	H304	May be fatal if swallowed and enters airways.
Aquatic Chronic 3	H412	Harmful to aquatic life with long lasting effects.

· 2.2 Label elements

· Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)



Printing date 24.09.2024 Version number 308 (replaces version 307) Revision: 24.09.2024

Trade name: Jump start spray E-COLL

(Contd. of page 1)

· Hazard pictograms





GHS02 GHS07

· Signal word Danger

· Hazard-determining components of labelling:

hydrocarbons, C6-C7, n-alkanes,

acetone

Hydrocarbons, C7, n-alkanes, isoalkanes, cycloalkanes

· Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P261 Avoid breathing spray.

P271 Use only outdoors or in a well-ventilated area. P302+P352 IF ON SKIN: Wash with plenty of water.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P312 Call a POISON CENTER/doctor if you feel unwell. P337+P313 If eye irritation persists: Get medical advice/attention.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· Additional information:

Buildup of explosive mixtures possible without sufficient ventilation.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

· PBT: Not applicable.

· vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.



Printing date 24.09.2024 Version number 308 (replaces version 307) Revision: 24.09.2024

Trade name: Jump start spray E-COLL

	(Cor	ntd. of page 2)
· Dangerous components:		
CAS: 75-28-5 EINECS: 200-857-2 Index number: 601-004-00-0 Reg.nr.: 01-2119485395-27-xxxx	isobutane Flam. Gas 1A, H220 Press. Gas (Comp.), H280	25-50%
CAS: 67-64-1 EINECS: 200-578-6 Index number: 603-002-00-5 Reg.nr.: 01-2119471330-49-xxxx 01-2119498062-37-xxxx	acetone Flam. Liq. 2, H225 Eye Irrit. 2, H319; STOT SE 3, H336 EUH066	10-<25%
CAS: 1634-04-4 EINECS: 216-653-1 Index number: 603-181-00-X	tert-butyl methyl ether Flam. Liq. 2, H225 Acute Tox. 3, H311 Skin Irrit. 2, H315	2.5-10%
CAS: 64742-49-0 EC number: 921-024-6 Reg.nr.: 01-2119475514-35-xxxx	hydrocarbons, C6-C7, n-alkanes, Flam. Liq. 2, H225 Asp. Tox. 1, H304 Aquatic Chronic 2, H411 Skin Irrit. 2, H315; STOT SE 3, H336	2.5-10%
CAS: 64742-49-0 EINECS: 265-151-9	Hydrocarbons, C7, n-alkanes, isoalkanes, cycloalkanes Flam. Liq. 2, H225 Asp. Tox. 1, H304 Aquatic Chronic 2, H411 Skin Irrit. 2, H315	2.5-10%
CAS: 74-98-6 EINECS: 200-827-9 Index number: 601-003-00-5 Reg.nr.: 01-2119486944-21-xxxx	propane Flam. Gas 1A, H220 Acute Tox. 1, H330 Press. Gas (Comp.), H280	2.5-10%
CAS: 106-97-8 EINECS: 203-448-7 Index number: 601-004-00-0 Reg.nr.: 01-2119474691-32-xxxx	butane, pure The Flam. Gas 1A, H220 Press. Gas (Comp.), H280	<1.25%
CAS: 67-56-1 EINECS: 200-659-6 Index number: 603-001-00-X	methanol	0.1-<1%

· Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · After inhalation: Supply fresh air.
- · After skin contact:

Immediately wash with water and soap and rinse thoroughly.

(Contd. on page 4)



Printing date 24.09.2024 Version number 308 (replaces version 307) Revision: 24.09.2024

Trade name: Jump start spray E-COLL

(Contd. of page 3)

If skin irritation continues, consult a doctor.

· After eve contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: Drink plenty of water and provide fresh air. Call for a doctor immediately.
- · 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters
- · Protective equipment: Do not inhale explosion gases or combustion gases.
- · Additional information Cool endangered receptacles with water spray.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

· 6.2 Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow product to reach sewage system or any water course.

Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Dispose contaminated material as waste according to section 13.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.



Printing date 24.09.2024 Version number 308 (replaces version 307) Revision: 24.09.2024

Trade name: Jump start spray E-COLL

(Contd. of page 4)

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Open and handle receptacle with care. Use only in well ventilated areas.

· Information about fire - and explosion protection:



Keep ignition sources away - Do not smoke.

Do not spray onto a naked flame or any incandescent material.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Store in a cool location.

Observe official regulations on storing packagings with pressurised containers.

- · Information about storage in one common storage facility: Store away from oxidising agents.
- · Further information about storage conditions:

Keep container tightly sealed.

Protect from heat and direct sunlight.

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· o.1 Control parameters		
· Ingredients with limit values that require monitoring at the workplace:		
CAS: 67-64-1 acetone		
IOELV Long-term value: 1210 mg/m³, 500 ppm		
CAS: 1634-04-4 tert-butyl methyl ether		
IOELV Short-term value: 367 mg/m³, 100 ppm Long-term value: 183.5 mg/m³, 50 ppm		
CAS: 67-56-1 methanol		
IOELV Long-term value: 260 mg/m³, 200 ppm Skin		
· DNELs		
CAS: 64742-49-0 hydrocarbons, C6-C7, n-alkanes,		
Oral DNEL Langzeitwert Verbraucher 699 mg/kg/d (cus)		

Diright Langzeitwert verbraucher 699 mg/kg/d (cus)

Dermal Long term value for employees 2,035 mg/m³ (industrial use)

(Contd. on page 6)



Printing date 24.09.2024 Version number 308 (replaces version 307) Revision: 24.09.2024

Trade name: Jump start spray E-COLL

(Contd. of page 5)

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see section 7.
- · Individual protection measures, such as personal protective equipment

· General protective and hygienic measures:

Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work.

· Respiratory protection:

Not necessary if room is well-ventilated.

Use suitable respiratory protective device in case of insufficient ventilation.

Self-contained respiratory protective device.

· Hand protection Recommendation: protective gloves

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Butyl rubber, BR

Recommended thickness of the material: ≥ 0.4 mm

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Not applicable, as aerosol.

Not applicable.

Eye/face protection Safety glasses

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Colour: Colourless · Odour: Ether-like · Odour threshold: Not determined. · Melting point/freezing point: Undetermined.

· Boiling point or initial boiling point and boiling

range

· Flammability

· Lower and upper explosion limit

· Lower: 1.4 Vol % · Upper: 13 Vol %

· Flash point: Not applicable, as aerosol.

170 °C · Auto-ignition temperature:

· Decomposition temperature: Not determined. · pH Not determined.

· Viscosity:

· Kinematic viscosity Not determined.

(Contd. on page 7)



Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 24.09.2024 Version number 308 (replaces version 307) Revision: 24.09.2024

Trade name: Jump start spray E-COLL

(Contd. of page 6)

· Kinematic: 23 °C - 4 mm (ISO 2431)

Not determined. · Dynamic:

· Solubility

· water Not miscible or difficult to mix.

· Partition coefficient n-octanol/water (log value) Not determined. · Vapour pressure at 20 °C: 3,000 hPa

· Density and/or relative density

· Density at 20 °C: 0.65 g/cm³ · Relative density Not determined. · Vapour density Not determined.

· 9.2 Other information

· Appearance:

· Form: Aerosol

· Important information on protection of health

and environment, and on safety.

· Ignition temperature: Product is not selfigniting. · Explosive properties: May form explosive peroxides.

· Solvent separation test:

· Organic solvents: 80.9 %

· Change in condition

· Drip point:

· Oxidising properties Not determined. · Evaporation rate Not applicable.

· Information with regard to physical hazard classes

· Explosives Void · Flammable gases Void

· Aerosols Extremely flammable aerosol. Pressurised container:

May burst if heated.

 Oxidising gases Void · Gases under pressure Void · Flammable liquids Void · Flammable solids Void · Self-reactive substances and mixtures Void · Pyrophoric liquids Void · Pyrophoric solids Void · Self-heating substances and mixtures Void · Substances and mixtures, which emit flammable gases in contact with water Void · Oxidising liquids Void · Oxidising solids Void · Organic peroxides Void · Corrosive to metals Void · Desensitised explosives Void

SECTION 10: Stability and reactivity

• 10.1 Reactivity No further relevant information available.



Printing date 24.09.2024 Version number 308 (replaces version 307) Revision: 24.09.2024

Trade name: Jump start spray E-COLL

(Contd. of page 7)

- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:
 No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 v	LD/LC50 values relevant for classification:				
CAS: 67-6	4-1 aceto	ne			
Oral	LD50	5,800 mg/kg (rat)			
Dermal	LD50	20,000 mg/kg (rabbit)			
Inhalative	LC50/4h	76 mg/m³ (rat)			
CAS: 1634	CAS: 1634-04-4 tert-butyl methyl ether				
Oral	LD50	4,000 mg/kg (rat)			
Dermal	LD50	1,000 mg/kg (rabbit)			
Inhalative	LC50/4h	142 ppm (rat)			
CAS: 64742-49-0 hydrocarbons, C6-C7, n-alkanes,					
Oral	LD50	>5,000 mg/kg (rat)			
Dermal	LD50	2,800-3,100 mg/kg (rat)			
Inhalative	LC50/4h	25.2 ppm (rat)			
CAS: 74-9	CAS: 74-98-6 propane				
Inhalative	LC50/4h	>20 mg/m³ (rat)			
CAS: 106-	CAS: 106-97-8 butane, pure				
Inhalative	LC50/4h	658 ppm (rat)			
CAS: 67-56-1 methanol					
Oral	LD50	5,628 mg/kg (rat)			
Dermal	LD50	15,800 mg/kg (rabbit)			

- · Primary irritant effect:
- · Skin corrosion/irritation

Causes skin irritation.

· Serious eye damage/irritation

Causes serious eye irritation.



Printing date 24.09.2024 Version number 308 (replaces version 307) Revision: 24.09.2024

Trade name: Jump start spray E-COLL

(Contd. of page 8)

- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure

May cause drowsiness or dizziness.

- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard

May be fatal if swallowed and enters airways.

- · 11.2 Information on other hazards
- · Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxi	· Aquatic toxicity:					
CAS: 75-28-5 isobutane						
EC50 (48h)	69.43 mg/L (daphnia)					
CAS: 67-64-	CAS: 67-64-1 acetone					
LC50 (96h)	5,000 mg/L (Lepomis macrochirus)					
LC50/48h	8,800 mg/l (Daphnia magna)					
NOEC	430 mg/l (algae)					
NOEC/16h	1,700 mg/l (Pseudomonas putida)					
NOEC/48h	4,740 mg/l (Pseudokirchneriella subcapitata)					
96h LC50	5,540 mg/l (Oncorhynchus mykiss)					
CAS: 64742-	CAS: 64742-49-0 hydrocarbons, C6-C7, n-alkanes,					
LC50 (96h)	1-10 mg/L (Pimephales promelas)					
EC50 (48h)	1-10 mg/L (daphnia)					
NOEC (21d)	1 mg/l (daphnia)					
NOEC	2.045 mg/l /28 Days (Oncorhynchus mykiss)					

- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.



Printing date 24.09.2024 Version number 308 (replaces version 307) Revision: 24.09.2024

Trade name: Jump start spray E-COLL

(Contd. of page 9)

- 12.6 Endocrine disrupting properties For information on endocrine disrupting properties see section 11.
- · 12.7 Other adverse effects
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:

Harmful to aquatic organisms

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods:

Containers can be recycled if completely empty; if not, dispose product/containers as dangerous waste. Observe local regulations.

· European waste catalogue

16 05 04* gases in pressure containers (including halons) containing hazardous substances

SECTION 14: Transport information

· 14.1 UN number or ID number

· ADR, IMDG, IATA UN1950

· 14.2 UN proper shipping name

· ADR UN1950 AEROSOLS

· IMDG, IATA AEROSOLS

· 14.3 Transport hazard class(es)

· ADR



· Class 2 5F Gases.

· Label 2.1

· IMDG, IATA



Class
 Label
 2 Gases.
 2.1

· 14.4 Packing group

· ADR, IMDG Void

(Contd. on page 11)



Printing date 24.09.2024 Version number 308 (replaces version 307) Revision: 24.09.2024

Trade name: Jump start spray E-COLL

(Contd. of page 10)

· 14.5 Environmental hazards:

· Marine pollutant: No

• 14.6 Special precautions for user Warning: Gases.

• **EMS Number**: F-D,S-U

· 14.7 Maritime transport in bulk according to IMO

instruments Not applicable.

· Transport/Additional information:

· ADR

Limited quantities (LQ)
 Transport category
 Tunnel restriction code

· UN "Model Regulation": UN1950, AEROSOLS, 2.1

SECTION 15: Regulatory information

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

· Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms





GHS02 GHS07

Signal word Danger

· Hazard-determining components of labelling:

hydrocarbons, C6-C7, n-alkanes,

acetone

Hydrocarbons, C7, n-alkanes, isoalkanes, cycloalkanes

· Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H315 Causes skin irritation.

H319 Causes serious eye irritation.H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P261 Avoid breathing spray.

P271 Use only outdoors or in a well-ventilated area. P302+P352 IF ON SKIN: Wash with plenty of water.

(Contd. on page 12)



Printing date 24.09.2024 Version number 308 (replaces version 307) Revision: 24.09.2024

Trade name: Jump start spray E-COLL

(Contd. of page 11)

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P312 Call a POISON CENTER/doctor if you feel unwell.
P337+P313 If eye irritation persists: Get medical advice/attention.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

- · Chemical safety assessment
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3, 69
- · REGULATION (EU) 2019/1148

The product contains: Reportable explosives precursors. Making available, transfer, possession and use in accordance with Regulation (EU) 2019/1148, Article 9.

 Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients are included.

- Annex II REPORTABLE EXPLOSIVES PRECURSORS CAS: 67-64-1 Acetone
- · National regulations:
- · Information about limitation of use:

Employment restrictions concerning pregnant and lactating women must be observed.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

aas.
1

H225 Highly flammable liquid and vapour.

H280 Contains gas under pressure; may explode if heated.

H301 Toxic if swallowed.

H304 May be fatal if swallowed and enters airways.

H311 Toxic in contact with skin.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H330 Fatal if inhaled.

H331 Toxic if inhaled.

H336 May cause drowsiness or dizziness.

H370 Causes damage to organs.

H371 May cause damage to organs.

H411 Toxic to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

· Department issuing SDS: Product safety department

· Contact: sdb@ede.de

Date of previous version: 21.11.2023
Version number of previous version: 307

Page 13/13



Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 24.09.2024 Version number 308 (replaces version 307) Revision: 24.09.2024

Trade name: Jump start spray E-COLL

(Contd. of page 12)

· Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH) LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Gas 1A: Flammable gases - Category 1A

Aerosol 1: Aerosols - Category 1

Press. Gas (Comp.): Gases under pressure - Compressed gas

Flam. Lig. 2: Flammable liquids - Category 2 Acute Tox. 3: Acute toxicity – Category 3
Acute Tox. 1: Acute toxicity – Category 1 Skin Irrit. 2: Skin corrosion/irritation - Category 2

Eye Irrit. 2: Serious eye damage/eye irritation - Category 2

STOT SE 1: Specific target organ toxicity (single exposure) - Category 1

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

* Data compared to the previous version altered.

EU -