

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 11.04.2023

Version number 310 (replaces version 309)

Revision: 11.04.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier** 600077
- **Trade name:** Zinc-aluminium spray E-COLL
- **Article number:** 4317784349161
- **UFI:** SJXX-FQ70-690T-EM4D
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
- **Sector of Use**
SU21 Consumer uses: Private households / general public / consumers
SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
- **Application of the substance / the mixture** Anticorrosion additive
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
E/D/E - Einkaufsbuero Deutscher Eisenhaendler GmbH
EDE Platz 1
D-42389 Wuppertal
Germany

Tel. +49 202 6096-0
e-mail: sdb@ede.de
- **Further information obtainable from:** Product safety department
- **1.4 Emergency telephone number:** Giftinformationszentrum Mainz – Tel.: +49 (6131) 19240

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**

Aerosol 1	H222-H229	Extremely flammable aerosol. Pressurised container: May burst if heated.
Eye Irrit. 2	H319	Causes serious eye irritation.
STOT SE 3	H336	May cause drowsiness or dizziness.
Aquatic Chronic 3	H412	Harmful to aquatic life with long lasting effects.

- **2.2 Label elements**

- **Labelling according to Regulation (EC) No 1272/2008**
The product is classified and labelled according to the CLP regulation.

- **Hazard pictograms**



GHS02 GHS07

- **Signal word** Danger

(Contd. on page 2)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 11.04.2023

Version number 310 (replaces version 309)

Revision: 11.04.2023

Trade name: Zinc-aluminium spray E-COLL

(Contd. of page 1)

Hazard-determining components of labelling:

acetone
ethyl acetate
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, aromatics (<2%)
Solvent naphtha (petroleum), light arom.

Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Do not pierce or burn, even after use.
P261 Avoid breathing spray.
P271 Use only outdoors or in a well-ventilated area.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337+P313 If eye irritation persists: Get medical advice/attention.
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking.

2.3 Other hazards
Results of PBT and vPvB assessment

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

- **Description:** Mixture of substances listed below with nonhazardous additions.

Dangerous components:

CAS: 106-97-8 EINECS: 203-448-7 Index number: 601-004-00-0 Reg.nr.: 01-2119474691-32-xxxx	butane, pure ⚠ Flam. Gas 1A, H220 Press. Gas (Comp.), H280	25-<50%
CAS: 67-64-1 EINECS: 200-662-2 Index number: 606-001-00-8 Reg.nr.: 01-2119471330-49-xxxx 01-2119498062-37-xxxx	acetone ⚠ Flam. Liq. 2, H225 ⚠ Eye Irrit. 2, H319; STOT SE 3, H336 EUH066	10-<25%

(Contd. on page 3)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 11.04.2023

Version number 310 (replaces version 309)

Revision: 11.04.2023

Trade name: Zinc-aluminium spray E-COLL

(Contd. of page 2)

CAS: 74-98-6 EINECS: 200-827-9 Index number: 601-003-00-5 Reg.nr.: 01-2119486944-21-xxxx	propane ⚠ Flam. Gas 1A, H220 Press. Gas (Comp.), H280	10-<25%
CAS: 141-78-6 EINECS: 205-500-4 Index number: 607-022-00-5 Reg.nr.: 01-2119475103-46-xxxx	ethyl acetate ⚠ Flam. Liq. 2, H225 ⚠ Eye Irrit. 2, H319; STOT SE 3, H336 EUH066	10-<25%
CAS: 1330-20-7 EINECS: 215-535-7 Index number: 601-022-00-9 Reg.nr.: 01-2119488216-32-xxxx	xylene ⚠ Flam. Liq. 3, H226 ⚠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	1-<5%
CAS: 7429-90-5 EINECS: 231-072-3 Index number: 013-002-00-1 Reg.nr.: 01-2119529243-45	aluminium powder (stabilised) ⚠ Flam. Sol. 1, H228	1-<5%
EC number: 919-857-5 Index number: 649-327-00-6 Reg.nr.: 01-2119463258-33-xxxx	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, aromatics (<2%) ⚠ Flam. Liq. 3, H226 ⚠ Asp. Tox. 1, H304 ⚠ STOT SE 3, H336 EUH066	1-<5%
CAS: 7440-66-6 EINECS: 231-175-3 Index number: 030-001-01-9 Reg.nr.: 01-2119467174-37	zinc powder -zinc dust (stabilized) ⚠ Aquatic Acute 1, H400; Aquatic Chronic 1, H410	1-<5%
CAS: 64742-95-6 EC number: 918-668-5 Index number: 649-356-00-4 Reg.nr.: 01-2119455851-35-xxxx	Solvent naphtha (petroleum), light arom. ⚠ Flam. Liq. 3, H226 ⚠ Asp. Tox. 1, H304 ⚠ Aquatic Chronic 2, H411 ⚠ STOT SE 3, H335-H336	1-<5%

- **Additional information:** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

• 4.1 Description of first aid measures

- **After inhalation:** Supply fresh air.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** Drink plenty of water and provide fresh air. Call for a doctor immediately.

• 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

(Contd. on page 4)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 11.04.2023

Version number 310 (replaces version 309)

Revision: 11.04.2023

Trade name: Zinc-aluminium spray E-COLL

(Contd. of page 3)

· 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures**· 5.1 Extinguishing media****· Suitable extinguishing agents:**CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.**· For safety reasons unsuitable extinguishing agents:** Water with full jet**· 5.2 Special hazards arising from the substance or mixture** Can form explosive gas-air mixtures.**· 5.3 Advice for firefighters****· Protective equipment:**

Do not inhale explosion gases or combustion gases.

Wear self-contained respiratory protective device.

· Additional information Cool endangered receptacles with water spray.**SECTION 6: Accidental release measures****· 6.1 Personal precautions, protective equipment and emergency procedures**

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

· 6.2 Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Do not flush with water or aqueous cleansing agents

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage**· 7.1 Precautions for safe handling**

Open and handle receptacle with care.

Use only in well ventilated areas.

(Contd. on page 5)

EU

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 11.04.2023

Version number 310 (replaces version 309)

Revision: 11.04.2023

Trade name: Zinc-aluminium spray E-COLL

(Contd. of page 4)

Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Do not spray onto a naked flame or any incandescent material.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

7.2 Conditions for safe storage, including any incompatibilities**Storage:****Requirements to be met by storerooms and receptacles:**

Store in a cool location.

Observe official regulations on storing packagings with pressurised containers.

Information about storage in one common storage facility: Store away from oxidising agents.**Further information about storage conditions:**

Keep container tightly sealed.

Protect from heat and direct sunlight.

7.3 Specific end use(s) No further relevant information available.*** SECTION 8: Exposure controls/personal protection****8.1 Control parameters****Ingredients with limit values that require monitoring at the workplace:****CAS: 67-64-1 acetone**IOELV Long-term value: 1210 mg/m³, 500 ppm**CAS: 141-78-6 ethyl acetate**IOELV Short-term value: 1468 mg/m³, 400 ppm
Long-term value: 734 mg/m³, 200 ppm**CAS: 1330-20-7 xylene**IOELV Short-term value: 442 mg/m³, 100 ppm
Long-term value: 221 mg/m³, 50 ppm
Skin**Additional information:** The lists valid during the making were used as basis.**8.2 Exposure controls****Appropriate engineering controls** No further data; see section 7.**Individual protection measures, such as personal protective equipment****General protective and hygienic measures:**

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

(Contd. on page 6)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 11.04.2023

Version number 310 (replaces version 309)

Revision: 11.04.2023

Trade name: Zinc-aluminium spray E-COLL

(Contd. of page 5)

Avoid contact with the eyes.

· Respiratory protection:

Not necessary if room is well-ventilated.

Use suitable respiratory protective device in case of insufficient ventilation.

Self-contained respiratory protective device.

· Hand protection

Protective gloves

· Material of gloves

Butyl rubber, BR

Recommended thickness of the material: ≥ 0.4 mm

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye/face protection

Tightly sealed goggles

· Body protection: Solvent resistant protective clothing*** SECTION 9: Physical and chemical properties****· 9.1 Information on basic physical and chemical properties****· General Information****· Physical state**

Aerosol

· Colour:

Grey

· Odour:

Characteristic

· Odour threshold:

Not determined.

· Melting point/freezing point:

-187 °C

· Boiling point or initial boiling point and boiling range

Not applicable, as aerosol.

· Flammability

Extremely flammable aerosol.

The mixture is capable of catching fire or being set on fire.

The substance is capable of catching fire or being set on fire.

· Lower and upper explosion limit**· Lower:**

1.1 Vol %

· Upper:

15 Vol %

· Flash point:

Not applicable, as aerosol.

· Auto-ignition temperature:

>200 °C

· Decomposition temperature:

Not determined.

· pH

Not determined.

(Contd. on page 7)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 11.04.2023

Version number 310 (replaces version 309)

Revision: 11.04.2023

Trade name: Zinc-aluminium spray E-COLL

(Contd. of page 6)

· Viscosity:	
· Kinematic viscosity	Not determined.
· Kinematic: 23 °C - 4 mm (ISO 2431)	
· Dynamic:	Not determined.
· Solubility	
· water:	Not miscible or difficult to mix.
· Partition coefficient n-octanol/water (log value)	Not determined.
· Vapour pressure at 20 °C:	7,400 hPa
· Density and/or relative density	
· Density at 20 °C:	0.68 g/cm ³
· Relative density	Not determined.
· Vapour density	Not determined.
· 9.2 Other information	
· Appearance:	
· Form:	Aerosol
· Important information on protection of health and environment, and on safety.	
· Ignition temperature:	Product is not selfigniting.
· Explosive properties:	Not determined.
· Solvent separation test:	
· VOC (EC) %	95.50 %
· VOC (EC) g/l	655.2 g/l
· Change in condition	
· Drip point:	
· Oxidising properties	Not determined.
· Evaporation rate	Not applicable.
· Information with regard to physical hazard classes	
· Explosives	Void Void
· Flammable gases	Void Void
· Aerosols	Extremely flammable aerosol. Pressurised container: May burst if heated. Void
· Oxidising gases	Void Void
· Gases under pressure	Void Void
· Flammable liquids	Void Void
· Flammable solids	Void Void
· Self-reactive substances and mixtures	Void Void
· Pyrophoric liquids	Void Void
· Pyrophoric solids	Void Void
· Self-heating substances and mixtures	Void Void

(Contd. on page 8)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 11.04.2023

Version number 310 (replaces version 309)

Revision: 11.04.2023

Trade name: Zinc-aluminium spray E-COLL

(Contd. of page 7)

- **Substances and mixtures, which emit flammable gases in contact with water** Void
- **Oxidising liquids** Void
- **Oxidising solids** Void
- **Organic peroxides** Void
- **Corrosive to metals** Void
- **Desensitised explosives** Void

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:**CAS: 106-97-8 butane, pure**

Inhalative	LC50/4h	658 ppm (rat)
------------	---------	---------------

CAS: 67-64-1 acetone

Oral	LD50	5,800 mg/kg (rat)
Dermal	LD50	20,000 mg/kg (rabbit)
Inhalative	LC50/4h	76 mg/m ³ (rat)

CAS: 74-98-6 propane

Inhalative	LC50/4h	>20 mg/m ³ (rat)
------------	---------	-----------------------------

CAS: 141-78-6 ethyl acetate

Oral	LD50	5,620 mg/kg (rabbit)
Inhalative	LC50/4h	1,600 ppm (rat)

(Contd. on page 9)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 11.04.2023

Version number 310 (replaces version 309)

Revision: 11.04.2023

Trade name: Zinc-aluminium spray E-COLL

(Contd. of page 8)

CAS: 1330-20-7 xylene		
Oral	LD50	4,300 mg/kg (rat)
Dermal	LD50	2,000 mg/kg (rabbit)
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, aromatics (<2%)		
Oral	LD50	>15,000 mg/kg (rat) (OECD 401)
Dermal	LD50	3,400 mg/kg (rat) (OECD 402)
Inhalative	LC50/4h	13,100 ppm (rat) (OECD 403)
CAS: 64742-95-6 Solvent naphtha (petroleum), light arom.		
Oral	LD50	>6,800 mg/kg (rat)
Dermal	LD50	>3,400 mg/kg (rab)
Inhalative	LC50/4h	>10.2 ppm (rat)

- **Skin corrosion/irritation** Based on available data, the classification criteria are not met.
- **Serious eye damage/irritation**
Causes serious eye irritation.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure**
May cause drowsiness or dizziness.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.
- **11.2 Information on other hazards**

· Endocrine disrupting properties

None of the ingredients is listed.

* SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity:

CAS: 67-64-1 acetone

LC50 (96h)	5,000 mg/L (Lepomis macrochirus)
LC50/48h	8,800 mg/l (Daphnia magna)
NOEC	430 mg/l (algae)
NOEC/16h	1,700 mg/l (Pseudomonas putida)
NOEC/48h	4,740 mg/l (Pseudokirchneriella subcapitata)
96h LC50	5,540 mg/l (Oncorhynchus mykiss)

(Contd. on page 10)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 11.04.2023

Version number 310 (replaces version 309)

Revision: 11.04.2023

Trade name: Zinc-aluminium spray E-COLL

(Contd. of page 9)

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, aromatics (<2%)

NOEC 24.3 mg/l (rat)

- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Endocrine disrupting properties** For information on endocrine disrupting properties see section 11.
- **12.7 Other adverse effects**
- **Remark:** Harmful to fish
- **Additional ecological information:**
- **General notes:**
Harmful to aquatic organisms
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods:**

· **European waste catalogue**

16 05 04* gases in pressure containers (including halons) containing hazardous substances

SECTION 14: Transport information

- **14.1 UN number or ID number**
- **ADR, IMDG, IATA** UN1950
- **14.2 UN proper shipping name**
- **ADR** UN1950 AEROSOLS
- **IMDG, IATA** AEROSOLS
- **14.3 Transport hazard class(es)**
- **ADR**
- 
- **Class** 2 5F Gases.

(Contd. on page 11)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 11.04.2023

Version number 310 (replaces version 309)

Revision: 11.04.2023

Trade name: Zinc-aluminium spray E-COLL

(Contd. of page 10)

· Label

2.1

· IMDG, IATA



· Class

2 Gases.

· Label

2.1

· 14.4 Packing group

· ADR

Void

· 14.5 Environmental hazards:

· Marine pollutant:

No

· 14.6 Special precautions for user

· EMS Number:

· Stowage Code

Warning: Gases.

F-D,S-U

SW1 Protected from sources of heat.

SW22 For AEROSOLS with a maximum capacity of 1

litre: Category A. For AEROSOLS with a capacity

above 1 litre: Category B. For WASTE AEROSOLS:

Category C, Clear of living quarters.

SG69 For AEROSOLS with a maximum capacity of 1

litre:

Segregation as for class 9. Stow "separated from"

class 1 except for division 1.4.

For AEROSOLS with a capacity above 1 litre:

Segregation as for the appropriate subdivision of class

2.

For WASTE AEROSOLS:

Segregation as for the appropriate subdivision of class

2.

· 14.7 Maritime transport in bulk according to IMO instruments

Not applicable.

· Transport/Additional information:

· ADR

· Limited quantities (LQ)

1L

· Excepted quantities (EQ)

Code: E0

Not permitted as Excepted Quantity

· Transport category

2

· Tunnel restriction code

D

· IMDG

· Limited quantities (LQ)

1L

· Excepted quantities (EQ)

Code: E0

Not permitted as Excepted Quantity

· UN "Model Regulation":

UN1950, AEROSOLS, 2.1

EU

(Contd. on page 12)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 11.04.2023

Version number 310 (replaces version 309)

Revision: 11.04.2023

Trade name: Zinc-aluminium spray E-COLL

(Contd. of page 11)

SECTION 15: Regulatory information

- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

- **Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the CLP regulation.

- **Hazard pictograms**



GHS02 GHS07

- **Signal word** Danger

- **Hazard-determining components of labelling:**

acetone

ethyl acetate

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, aromatics (<2%)

Solvent naphtha (petroleum), light arom.

- **Hazard statements**

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

- **Precautionary statements**

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P261 Avoid breathing spray.

P271 Use only outdoors or in a well-ventilated area.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337+P313 If eye irritation persists: Get medical advice/attention.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- **Directive 2012/18/EU**

- **Named dangerous substances - ANNEX I** Methanol

- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 150 t

- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t

- **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3

- **DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II**

None of the ingredients is listed.

(Contd. on page 13)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 11.04.2023

Version number 310 (replaces version 309)

Revision: 11.04.2023

Trade name: Zinc-aluminium spray E-COLL

(Contd. of page 12)

· Exposure scenario(s)

Exposure scenario(s) of ingredients (if present) are available on request at:
sdb@ede.de

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H220 Extremely flammable gas.
H225 Highly flammable liquid and vapour.
H226 Flammable liquid and vapour.
H228 Flammable solid.
H280 Contains gas under pressure; may explode if heated.
H304 May be fatal if swallowed and enters airways.
H312 Harmful in contact with skin.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H332 Harmful if inhaled.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.
H400 Very toxic to aquatic life.
H410 Very toxic to aquatic life with long lasting effects.
H411 Toxic to aquatic life with long lasting effects.
EUH066 Repeated exposure may cause skin dryness or cracking.

· Department issuing SDS: Product safety department**· Contact: sdb@ede.de****· Date of previous version: 19.11.2020****· Version number of previous version: 309****· Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
VOC: Volatile Organic Compounds (USA, EU)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Flam. Gas 1A: Flammable gases – Category 1A
Aerosol 1: Aerosols – Category 1
Press. Gas (Comp.): Gases under pressure – Compressed gas
Flam. Liq. 2: Flammable liquids – Category 2
Flam. Liq. 3: Flammable liquids – Category 3
Flam. Sol. 1: Flammable solids – Category 1
Acute Tox. 4: Acute toxicity – Category 4
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
Asp. Tox. 1: Aspiration hazard – Category 1
Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1
Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1

(Contd. on page 14)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 11.04.2023

Version number 310 (replaces version 309)

Revision: 11.04.2023

Trade name: Zinc-aluminium spray E-COLL

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

(Contd. of page 13)

· * **Data compared to the previous version altered.**

EU